



**Tripp Lite**  
1111 West 35th Street  
Chicago, IL 60609 USA  
Telephone: +(773) 869 1234  
E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: SM500RMNAFTA

### Smart Pro Rack/Tower UPS - NAFTA assembled version of SMART500RT1U

#### Highlights



- 500VA line interactive 1U rack/tower UPS
- 6 outlets with 1 switchable load bank
- Simultaneous communications via SNMPWEBCARD slot, USB and DB9 serial ports
- Included PowerAlert UPS monitoring software manages an unlimited number of network UPS systems
- Built-in voltage regulation corrects brownouts to 90V
- \$250,000 [Ultimate Lifetime Insurance](#) (USA, Puerto Rico & Canada only)

#### Description

Tripp Lite's SM500RMNAFTA intelligent, line interactive rack/tower uninterruptible power supply prevents data loss, downtime and equipment damage due to power outages, voltage fluctuations and transient surges. Requires only one rack space (1U) in a 2 or 4 post rack, with included accessories for upright tower placement. Large internal batteries offer 8 minutes half load runtime and 3 minutes at full load. Maintains regulated 120V nominal output without using battery power during brownouts as low as 90V. 500VA/300 watt power handling capability is compatible with networking, telecom and other sensitive electronic applications. Includes 6 UPS supported outlets with a single outlet load bank that can be individually controlled via software interface to reboot select equipment on demand or shed less significant loads to extend battery runtime for more critical equipment. Includes 1 surge-only outlet for peripherals not requiring battery backup. Supports simultaneous remote monitoring of UPS and site power conditions via built-in USB and DB9 monitoring ports. Includes PowerAlert UPS monitoring and unattended shutdown software with complete cabling. Built-in accessory slot supports SNMP with optional SNMPWEBCARD adapter. Emergency Power Off (EPO) interface offers option for instantaneous power-off of UPS and connected equipment in the case of fire or emergency situation. Multi-function audible alarms and set of 5 front panel LEDs offer at-a-glance notification of UPS and line power status. Network-grade AC surge suppression protects equipment from damage and performance problems resulting from transient surges and line noise. Attractive all-black color scheme. Two year warranty with \$250,000 [connected equipment insurance](#) (USA & Canada only).

#### Applications

Ideal for protection of file servers, network accessories and telecommunications equipment in server rooms, internetworking closets, co-location racks, kiosks and a variety of other locations. Common applications include any mix of servers, workstations, hubs, routers, concentrators, IP telephony and traditional PBX switching systems.

#### Package Includes

- SM500RMNAFTA UPS System
- Mounting hardware
- Cabling for USB & DB9 monitoring and EPO switching
- PowerAlert unattended shutdown and UPS/Power monitoring software
- Warranty information and instruction manual

#### Features

SM500RMNAFTA line interactive UPS offers battery derived sine wave AC output during power outages, voltage regulation during brownouts,

plus network-grade AC surge suppression

500VA/300 watt power handling capability compatible with networking, telecom and other sensitive electronic devices

Supports 1U rackmount installation in 2 or 4 post rack enclosures, upright tower placement also supported - mounting accessories included

Large internal batteries offer runtimes of 17 minutes at half load (250VA/150 watts) and 5 minutes at full load (500VA/300 watts)

Maintains regulated 120V nominal output during brownouts as low as 90V

Includes 6 UPS-supported outlets, with one pair of individually controllable outlets that can be powered off and back on again via software interface

PowerAlert UPS monitoring and unattended shutdown software enables configurable network broadcast messaging, pager & email notification, event logging and running user-defined script commands

Offers simultaneous monitoring by up to 3 directly-connected devices through included USB, DB9 and SNMP\* interfaces (\*requires optional SNMPWEBCARD), or the monitoring of any number of additional UPS systems over IP with included PowerAlert monitoring software. Free PowerAlert enterprise management software is also available for select opportunities

Communications ports support messaging of UPS and line power status, including on-battery, low-battery, power restored, AC line voltage, DC battery voltage and remaining battery capacity

Supports timed inverter shutoff after unattended shutdown, activate self-test and UPS output power control for scheduled or immediate reboot of connected devices

Supports Tripp Lite's WatchDog software application to restore unresponsive programs by systematically restarting applications, operating systems and ultimately rebooting completely locked computers by momentarily switching UPS power off and back on again (requires optional WATCHDOGSW)

Built-in accessory slot supports SNMP with optional SNMPWEBCARD adapter

Emergency Power Off (EPO) interface with cable

Multi-function audible alarms and set of 5 front panel LEDs

Network-grade AC surge suppression

Attractive all-black color scheme

UPS battery set ships fully assembled and ready for installation, no time consuming connection of internal batteries by user is necessary

Two year warranty with \$250,000 [connected equipment insurance](#) (USA & Canada only)

## Specifications

SYSTEM OVERVIEW	
Voltage compatibility	120 VAC
Frequency compatibility	60 Hz
OUTPUT	
Output VA	500
Output watts	300
Output nominal voltage	120V AC
Output voltage regulation	LINE MODE: Sine wave line voltage 120V (-15% +13%), BATTERY MODE: PWM sine wave output within 10% of 120V
Output frequency regulation	LINE MODE: Passes line frequency of 60Hz +/-10% BATTERY MODE: Inverter output regulated to 60Hz +/-1Hz
Outlet quantity / type	7 NEMA 5-15R
Customized load management receptacles	Includes single-outlet load bank that supports load shedding and remote reboot on demand of locked network devices. Controllable via PowerAlert software to switch off optional loads, like monitors, to increase available runtime for servers and other critical devices.
Overload protection	Via 15A input breaker
INPUT	
Maximum input amps	5.6A
Input connection type	NEMA 5-15P
Input cord length	10 ft., 14 gauge, Black
Recommended electrical service	15A 120V
BATTERY	

<b>Full load runtime</b>	3 minutes (500VA)
<b>Half load runtime</b>	8 minutes (250VA)
<b>DC system voltage</b>	12 VDC
<b>Typical battery lifespan</b>	3-6 years, depending on usage
<b>Battery recharge rate</b>	2-4 hours to 90%
<b>Replacement Battery Cartridge</b>	RBC62-1U
<b>VOLTAGE REGULATION</b>	
<b>Voltage regulation description</b>	Line interactive voltage regulation system corrects brownouts as low as 90 volts back to usable 120V nominal levels
<b>Brownout correction</b>	Input voltages between 90 and 108 are boosted by 14%
<b>LEDS ALARMS &amp; SWITCHES</b>	
<b>Front panel LEDs</b>	5 front panel LEDs - green POWER LED, green AVR LED, 3-color BATTERY CHARGE LED, 3-color OUTPUT LOAD LEVEL LED, red BATTERY WARNING LED.
<b>Alarms</b>	Audible alarm warns of power failure, overload, UPS fault and low battery conditions
<b>Switches</b>	Includes 2 front panel mounted push-button switches for system enable, self-test and alarm cancel functions
<b>SURGE / NOISE SUPPRESSION</b>	
<b>AC surge suppression</b>	480 joules
<b>AC suppression response time</b>	Instantaneous
<b>EMI / RFI AC noise suppression</b>	Yes
<b>PHYSICAL</b>	
<b>Shipping weight (lbs)</b>	19.9
<b>Shipping weight (kg)</b>	9
<b>Shipping Dimensions (HWD/in)</b>	5 x 22.5 x 16
<b>Shipping Dimensions (HWD/cm)</b>	12.7 x 57.2 x 40.6
<b>Unit weight (lbs)</b>	17.6
<b>Unit weight (kg)</b>	8
<b>Unit Dimensions (HWD/in)</b>	1.75 x 17.5 x 11.75
<b>Unit Dimensions (HWD/cm)</b>	4.45 x 44.5 x 29.8
<b>Material of construction</b>	Steel
<b>Form factors supported</b>	Rack (1U)
<b>Battery Access</b>	Battery access door allows hot swap battery replacement without powering connected equipment off
<b>ENVIRONMENTAL</b>	
<b>Operating Temperature</b>	+32 to +104 degrees Fahrenheit / 0 to +40 degrees Celsius
<b>Storage Temperature</b>	+5 to +122 degrees Fahrenheit / -15 to +50 degrees Celsius
<b>Relative Humidity</b>	0 to 95%, non-condensing

<b>Line mode BTU/hr. (Max.)</b>	65.1
<b>Battery mode BTU/hr. (Max.)</b>	437.1
<b>COMMUNICATIONS</b>	
<b>Network monitoring port</b>	Includes 2 built-in monitoring ports, 1-USB & 1-DB9. Each supports on battery, low battery, power restored, AC line voltage, DC battery voltage, load percentage, battery charge current, battery capacity, internal UPS temperature and line frequency status
<b>Software and cabling included</b>	Includes PowerAlert UPS monitoring software for network and standalone operating systems. Ships with complete USB and DB9 cabling.
<b>SNMP compatibility</b>	Built-in accessory slot accommodates internal SNMP / Web card and other network accessories
<b>WatchDog compatibility</b>	Yes, compatible with Tripp Lite's Watchdog system service to restore operation to locked equipment through soft reboot of application / OS or hard power off/on reboot of connected equipment - ideal for unattended kiosk applications
<b>LINE / BATTERY TRANSFER</b>	
<b>Transfer time from line power to battery mode</b>	2-4 milliseconds
<b>Low voltage transfer to battery power</b>	90V (resets to line power as line voltage increases to 94V or higher)
<b>High voltage transfer to battery power</b>	136V (resets to line power as line voltage decreases to 132 or lower)
<b>CERTIFICATIONS</b>	
<b>Certifications</b>	Tested to UL1778 (USA), cUL (Canada), Class B (emissions), NOM (Mexico), RoHS-Compliant
<b>WARRANTY</b>	
<b>Product warranty</b>	\$250,000 connected equipment insurance (USA / Canada only)
<b>Connected equipment insurance (USA and Canada Only)</b>	3 year, 5 year, next day and on-site warranty coverage available for select opportunities
<b>Optional coverage</b>	2 year product warranty
<b>SPECIAL FEATURES</b>	
<b>EPO port</b>	Includes RJ11 EPO (emergency power off) port and cable
<b>TVSS grounding</b>	Includes back panel grounding point with thumbscrew for data line surge suppressors and other network accessories requiring a safe grounding point
<b>Cold Start</b>	Yes, inverter can be "cold started" to enable temporary AC output during a power failure
<b>Appearance</b>	Attractive all-black color scheme

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/products/model.cfm?txtModelID=3531](http://www.tripplite.com/products/model.cfm?txtModelID=3531).