



**Tripp Lite**  
1111 West 35th Street  
Chicago, IL 60609 USA  
Telephone: +(773) 869 1234  
E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: SMART3000VS

### SmartPro Expandable Tower UPS System - Intelligent, line-interactive network power management system



#### Highlights

- 3000VA / 3kVA line interactive, extended-run tower UPS
- Maintains 120V nominal output over an input range of 79 to 147V
- Network communications supported via 2 USB ports, 2 serial ports, SNMP/Web card slot and EPO interface
- Current monitoring and switched PDU control via 3 two-outlet load banks
- Input: L5-30P (120V 30A / includes 5-20P plug 120V 20A) / Output: 1 L5-30R, 2 NEMA 5-15/20R, 7 NEMA 5-15R (120V)
- 2 year product warranty / \$250,000 [Ultimate Lifetime Insurance](#) (USA, Puerto Rico & Canada only)

#### Description

Tripp Lite's SMART 3000VS intelligent, line interactive UPS with expandable runtime protects server, networking and telecommunications equipment from blackouts, voltage fluctuations and transient surges. Small footprint, tower UPS system occupies only 106 square inches of floorspace with a height of only 14.25 inches. Large capacity 3000 VA/2250 watt rated UPS system offers 4 minutes runtime at full load and 14 minutes at half load during power failures. Runtime is expandable with optional external battery packs. Line interactive voltage regulation corrects brownouts as low as 79V and overvoltages as high as 147V to fully regulated 120V nominal output for smooth continuous operation of connected equipment. Includes a total of 10 outlets, 3 of which can be individually powered off and back on via software interface to selectively reboot remote equipment or shed less critical loads to extend battery runtime for more critical loads. Includes slot for internal SNMPWEBCARD, plus 2 DB9 and 2 USB enhanced monitoring ports for unattended shutdown, remote control and monitoring of UPS system and power data. Ships in attractive gray color scheme. Compatible with Tripp Lite's PowerAlert and Watchdog service software. 2 year warranty. \$250,000 [connected equipment insurance](#).

#### Applications

Ideal for protection of sensitive electronics in any application calling for upright tower UPS protection. Common applications include any mix of servers, workstations, hubs, routers, concentrators, IP telephony and traditional PBX switching systems.

#### Package Includes

SMART 3000VS UPS System, PowerAlert Software and cabling, Warranty information, Instruction manual

#### Features

- 3000VA/2250 watt output capacity accommodates a variety of server, networking and telecom devices
- High power density 3kVA UPS system occupies only 106 square inches of floorspace with a height of only 14.25 inches
- Compatible with North American 120V/60 Hz power as found in the USA, Canada and Mexico
- Offers 4 minutes runtime with a full load of 3000VA and 14 minutes with a half load of 1500VA
- Runtime is expandable with BP48V24-2U (limit 1) or BP48V60RT3U (multi-pack compatible) external battery packs
- Line interactive voltage regulation corrects severe brownouts and overvoltages from 79 to 147v back to normal 120v levels without using battery power
- 10 total outlets (7 NEMA5-15R; 2 NEMA5-15/20R; 1 L5-30R)
- Includes NEMA L5-30P locking 30 amp input plug connection; includes user installable NEMA 5-20P replacement plug to enable connection to a 20A circuit

Notification of system status via 5 LEDs and multi-function audible alarms

Included PowerAlert Software provides e-mail notification of power problems and the simultaneous automatic unattended shutdown of multiple servers

4 built-in communications ports (2-DB9, 2-USB) for remote monitoring and unattended shutdown

Slot for SNMP/web card (part#: SNMPWEBCARD) and environmental sensor (part#: ENVIROSENSE) for remote communications in large IP environments

Supports Tripp Lite's WatchDog software application to restore unresponsive programs by automatically restarting them and rebooting completely locked computers by automatically switching UPS power off and back on again

Communication ports support on battery, low battery, power restored, AC line voltage, DC battery voltage, load percentage, battery charge current, battery capacity, internal UPS temperature and line frequency status messaging. Interface supports timed inverter shutoff after unattended shutdown, activate self-test and 10 second reboot of connected equipment

3 individual customized load management receptacles can be individually powered off and back on again via software interface to reboot remote equipment or perform "load shedding" of less critical loads to extend battery runtime for the most critical equipment

Built-in Emergency Power Off (EPO) interface supports emergency shutoff in large facilities

Hot-swappable/user replaceable batteries allow on-site battery replacement through the front panel without powering off connected equipment or removing the UPS from the rack

UPS battery set ships fully assembled and ready for use, no time consuming, connection of individual internal batteries by user is necessary

UL (USA), cUL (Canada), NOM (Mexico), FCC Class A

\$250,000 [Ultimate Lifetime Insurance](#). No warranty cards required for coverage!

2 year manufacturer's product warranty

## Specifications

SYSTEM OVERVIEW	
Voltage compatibility	120V AC
Frequency compatibility	60 Hz
OUTPUT	
Output VA	3000
Output watts	2250
Output nominal voltage	120V AC
Output voltage regulation	LINE MODE: Sine wave line voltage 120V (-18% / +8%), BATTERY MODE: PWM sine wave output 120V +/-5%
Output frequency regulation	LINE MODE: Passes line frequency of 60Hz +/-10% BATTERY MODE: Inverter output regulated to 60Hz +/-0.5Hz
Outlet quantity / type	7 NEMA 5-15R, 2 NEMA 5-20R and 1 NEMA L5-30R
Customized load management receptacles	"3 individually controllable outlets support load shedding and remote reboot on demand of locked network devices. Controllable via PowerAlert software to switch off optional loads, like monitors, to increase available runtime for servers and other critical devices. "
Overload protection	Via 30A input breaker and 2 15A output breakers
INPUT	
Maximum input amps	24 amps
Input connection type	NEMA L5-30P
Input cord length	8 ft.
Recommended electrical service	120V 30A
BATTERY	
Full load runtime	4 minutes
Half load runtime	14 minutes
Expandable battery runtime	Runtime is expandable with BP48V24-2U (limit 1) or BP48V60RT3U (multi-pack compatible) external battery packs
DC system voltage	48 VDC

Typical battery lifespan	3-6 years, depending on usage
Battery recharge rate	2-4 hours to 90%
Replacement Battery Cartridge	RBC54
<b>VOLTAGE REGULATION</b>	
Voltage regulation description	Automatic Voltage Regulation (AVR) circuits maintain clean, regulated computer-grade 120V nominal output, without using battery power, during brownouts to 79V and overvoltages to 147V
Overvoltage correction	Input voltages between 128 and 147VAC are reduced by 12%
Direct pass through	Input voltages between 105 and 127VAC are passed on to connected equipment unchanged
Brownout correction	Input voltages between 95 and 104VAC are boosted by 12%
Severe brownout correction	Input voltages between 79 and 94VAC are boosted by 24%
<b>LEDS ALARMS &amp; SWITCHES</b>	
Front panel LEDs	Includes 5 front panel LEDs to indicate BATTERY CHARGE LEVEL, AC LINE POWER STATUS, VOLTAGE REGULATION STATUS, UPS LOAD LEVEL and BATTERY LOW / REPLACE information
Alarms	3 function audible alarm indicates power failure conditions (4 short beeps every 10 seconds), overload (continuous short beeps) and low battery (continuous tone)
Switches	Yes, includes 2 front panel mounted push-button switches for system enable, self-test and alarm cancel functions. Also includes rear panel CHARGE LEVEL switch.
<b>SURGE / NOISE SUPPRESSION</b>	
AC surge suppression	480 joules
AC suppression response time	Instantaneous
EMI / RFI AC noise suppression	Yes
<b>PHYSICAL</b>	
Shipping weight (lbs)	66
Shipping weight (kg)	30
Shipping Dimensions (HWD/in)	16 x 14.75 x 19.75
Shipping Dimensions (HWD/cm)	40.6 x 37.5 x 50.2
Unit weight (lbs)	59
Unit weight (kg)	26.8
Unit Dimensions (HWD/in)	14.25 x 9.25 x 12
Unit Dimensions (HWD/cm)	36.2 x 23.5 x 30.5
Material of construction	Polycarbonate
Form factors supported	Tower
Cooling method	Built-in cooling fan
Battery Access	Battery access door enables user battery replacement, hot-swappable battery replacement supported
<b>ENVIRONMENTAL</b>	
Operating Temperature	+32 to +104 degrees Fahrenheit / 0 to +40 degrees Celsius

<b>Storage Temperature</b>	+5 to +122 degrees Fahrenheit / -15 to +50 degrees Celsius
<b>Relative Humidity</b>	0 to 95%, non-condensing
<b>COMMUNICATIONS</b>	
<b>Network monitoring port</b>	Includes 4 built-in monitoring ports, 2-USB & 2-DB9. Each supports on battery, low battery, power restored, AC line voltage, DC battery voltage, load percentage, battery charge current, battery capacity, internal UPS temperature and line frequency status
<b>Software and cabling included</b>	Includes PowerAlert UPS monitoring software for all common network and standalone operating systems. Ships with 2 USB and 2 DB9 serial cables
<b>SNMP compatibility</b>	Built-in accessory slot accommodates internal SNMP / Web card and other network accessories
<b>WatchDog compatibility</b>	Yes, compatible with Tripp Lite's Watchdog system service to restore operation to locked equipment through soft reboot of application / OS or hard power off/on reboot of connected equipment - ideal for unattended kiosk applications
<b>LINE / BATTERY TRANSFER</b>	
<b>Transfer time from line power to battery mode</b>	2-4 milliseconds
<b>Low voltage transfer to battery power</b>	79V (resets to line power as voltage increases to 82V)
<b>High voltage transfer to battery power</b>	147V (resets to line power as voltage decreases to 143V)
<b>CERTIFICATIONS</b>	
<b>Certifications</b>	Tested to UL1778 (USA), cUL (Canada), FCC Class A (emissions), NOM (Mexico)
<b>WARRANTY</b>	
<b>Product warranty</b>	2 year product warranty
<b>Connected equipment insurance (USA and Canada Only)</b>	\$250,000 connected equipment insurance (USA / Canada only)
<b>Optional coverage</b>	3 year, 5 year, next day and on-site warranty coverage available for select opportunities - contact Tripp Lite for more information
<b>SPECIAL FEATURES</b>	
<b>EPO port</b>	Includes RJ11 EPO (emergency power off) port and interconnection cable
<b>Appearance</b>	Attractive gray tower UPS
<b>BATTERY PACK ACCESSORY (optional)</b>	
<b>Battery Pack Accessory (optional)</b>	BP48V24-2U (limit 1) or BP48V60RT3U (multi-pack compatible)

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/products/model.cfm?txtModelID=2721](http://www.tripplite.com/products/model.cfm?txtModelID=2721).