



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: SMART1500

SmartPro Tower UPS System - Intelligent, line interactive network power management system



Highlights

- 1500VA / 1.5kVA line interactive tower UPS
- Maintains 120V nominal output over an input range of 75 to 147V
- Network communications supported via USB port, serial port
- Input: NEMA 5-15P (120V 15A) / Output: 6 NEMA 5-15R (120V)
- 2 year product warranty / \$250,000 [Ultimate Lifetime Insurance](#) (USA, Puerto Rico & Canada only)

Description

Tripp Lite's SMART1500 intelligent, line interactive UPS system protects servers, networking accessories and telecommunications equipment from blackouts, voltage fluctuations and transient surges. Large internal batteries offer 20 minutes half load runtime and 7 minutes at full load during power failures. 1500VA/980 watt power handling capability supports a variety of networking, telecom and various other application types, including the support of multiple network workstations. Includes a total of 6 outlets, 1 of which can be individually powered on and off via software interface to selectively reboot remote equipment or to automatically shed less significant loads to extend battery runtime for more critical equipment. Supports remote monitoring of UPS and site power conditions via built-in USB and DB9 monitoring ports. Includes PowerAlert UPS monitoring and unattended shutdown software with complete cabling. Supports SNMP with optional SNMPWEBSOLO external adapter. Built-in audible alarm and 5 front panel LEDs indicate status of line power, battery power, battery low/replace, voltage regulation and load level. Wall mountable with optional UPSWM wallmount bracket. Network-grade AC surge suppression protects equipment from damage and performance problems resulting from transient surges. Attractive, small-footprint tower housing uses less than 66 square inches of floor or desktop space. Two year warranty with \$250,000 [connected equipment insurance](#) (USA & Canada Only).

Applications

Ideal for the protection of file servers, network accessories and telecommunications equipment. Common applications include any mix of servers, workstations, hubs, routers, concentrators, IP telephony and traditional PBX switching systems. Ideal for sensitive electronic applications in areas where brownouts and overvoltages are common.

Package Includes

- SMART1500 UPS System
- USB and DB9 monitoring cables
- PowerAlert unattended shutdown and UPS/Power monitoring software
- Instruction manual with warranty information

Features

- 1500VA/980 watt power handling capability supports a variety of networking, telecom and various other application types
- Built-in voltage regulation and battery support, plus complete AC suppression prevents equipment damage, data loss and downtime
- Large internal batteries offer 20 minutes half load runtime and 7 minutes at full load during power failures
- Automatic Voltage Regulation (AVR) circuits with two boost and one voltage reduction level maintains usable 120V nominal output over an input voltage range of 75-147V

Includes a total of 6 NEMA5-15R outlets, 1 of which can be individually powered on and off via software interface to selectively reboot remote equipment or shed less significant loads to extend battery runtime for more critical equipment

Includes 1 USB and 1 DB9 monitoring port for remote monitoring of UPS status and site power conditions

Communications ports enable safe unattended shutdown without data loss during extended power failures

Communications ports support messaging of UPS and line power status, including on-battery, low-battery, power-restored, AC line voltage, DC battery voltage and battery capacity

Communications ports support timed inverter shutoff after unattended shutdown, activate self-test and 10 second reboot of connected equipment

PowerAlert UPS monitoring and unattended shutdown software with complete cabling included

Supports Tripp Lite's WatchDog software application to restore unresponsive programs by automatically restarting them and rebooting completely locked computers by automatically switching UPS power off and back on again

Notification of system status via 5 LEDs and multi-function audible alarms

Wall mountable with UPSWM wallmount bracket

Attractive small footprint beige tower housing uses less than 66 square inches

Hot-swappable/user replaceable batteries allow on-site battery replacement

Cold start capability enables UPS turn-on in battery mode during blackout conditions

UL (USA), cUL (Canada), NOM (Mexico), Class A (Emissions)

\$250,000 [Ultimate Lifetime Insurance](#) (USA and Canada only)

2 year manufacturers product warranty with \$250,000 [connected equipment insurance](#) (USA & Canada Only)

Specifications

SYSTEM OVERVIEW	
Voltage compatibility	120V AC
Frequency compatibility	60 Hz
OUTPUT	
Output VA	1500
Output watts	980
Output nominal voltage	120V AC
Output voltage regulation	LINE MODE: Sine wave line voltage 120V (-18% / +8%) BATTERY MODE: PWM sine wave output 115V +/-5%
Output frequency regulation	LINE MODE: Passes line frequency of 60Hz +/-10% BATTERY MODE: Inverter output regulated to 60Hz +/-0.5Hz
Outlet quantity / type	6 NEMA 5-15R
Customized load management receptacles	"Individually controllable outlet supports load shedding and remote reboot on demand of locked network devices. Controllable via PowerAlert software to switch off optional loads, like monitors, to increase available runtime for servers and other critical devices."
Overload protection	Circuit breaker
INPUT	
Maximum input amps	12A / 1070 watts
Input connection type	NEMA 5-15P
Input cord length	6 ft., 14 gauge
Recommended electrical service	15A 120V
BATTERY	
Full load runtime	7 minutes (1500VA)
Half load runtime	20 minutes (750VA)

DC system voltage	36 V DC
Typical battery lifespan	3-6 years, depending on usage
Battery recharge rate	2-4 hours to 90%
Replacement Battery Cartridge	RBC53
VOLTAGE REGULATION	
Voltage regulation description	Automatic Voltage Regulation (AVR) circuits maintain clean, regulated computer-grade 120V nominal output, without using battery power, during brownouts to 75V and overvoltages to 147V
Overvoltage correction	Input voltages between 128 and 147V AC are reduced by 12%
Direct pass through	Input voltages between 108 and 127V AC are passed on to connected equipment unchanged
Brownout correction	Input voltages between 93 and 107V AC are boosted by 14%
Severe brownout correction	Input voltages between 75 and 92V AC are boosted by 30%
LEDS ALARMS & SWITCHES	
Front panel LEDs	Includes 5 front panel LEDs to indicate BATTERY CHARGE LEVEL, AC LINE POWER STATUS, VOLTAGE REGULATION STATUS, UPS LOAD LEVEL and BATTERY LOW / REPLACE information
Alarms	Audible alarm indicates power failure conditions (4 short beeps every 10 seconds), overload (continuous short beeps) and low battery (continuous tone)
Switches	Yes, includes 2 front panel mounted push-button switches for system enable, self-test and alarm cancel functions
SURGE / NOISE SUPPRESSION	
AC surge suppression	480 joules
AC suppression response time	Instantaneous
EMI / RFI AC noise suppression	Yes
PHYSICAL	
Shipping weight (lbs)	42.6
Shipping weight (kg)	19.4
Unit weight (lbs)	38.4
Unit weight (kg)	17.5
Unit Dimensions (HWD/in)	12.75 x 7.5 x 9
Unit Dimensions (HWD/cm)	32.4 x 19.1 x 22.9
Material of construction	PVC
Form factors supported	Tower, wall mountable with optional UPSWM accessory
Cooling method	Built-in rear exit cooling fan
Battery Access	Battery access door allows hot swap battery replacement without powering connected equipment off
ENVIRONMENTAL	

Operating Temperature	+32 to +104 degrees Fahrenheit
Storage Temperature	+5 to +122 degrees Fahrenheit
Relative Humidity	0 to 95%, non-condensing
COMMUNICATIONS	
Network monitoring port	Includes 2 built-in monitoring ports, 1-USB & 1-DB9. Each supports on battery, low battery, power restored, AC line voltage, DC battery voltage, load percentage, battery charge current, battery capacity, internal UPS temperature, line frequency status messaging. Interface supports timed inverter shutoff after unattended shutdown, activate self-test and 10 second reboot of connected equipment. Supports individual reboot of selected items connected to load management receptacles and load shedding to increase battery runtime for the most critical loads. Compatible with Tripp Lite's PowerAlert and Watchdog service software.
Software and cabling included	Includes PowerAlert UPS monitoring software for all common network and standalone operating systems. Ships with 2 cables, 1-USB to USB & 1-DB9 to DB9
SNMP compatibility	Yes via external SNMP adapter accessory #SNMPWEBSOLO
WatchDog compatibility	Yes, compatible with Tripp Lite's Watchdog system service to restore operation to locked equipment through soft reboot of application / OS or hard power off/on reboot of connected equipment - ideal for unattended kiosk applications
LINE / BATTERY TRANSFER	
Transfer time from line power to battery mode	2-4 milliseconds
Low voltage transfer to battery power	Switches to battery power as line voltage decreases to 75 volts or less. Resets back to line power mode as line voltage increases to 79V or higher.
High voltage transfer to battery power	Switches to battery power as line voltage increases to 147 volts or higher. Resets back to line power mode as line voltage decreases to 143V or less.
CERTIFICATIONS	
Certifications	Tested to UL1778 (USA), cUL (Canada), Class A (emissions), NOM (Mexico)
WARRANTY	
Product warranty	2 year product warranty
Connected equipment insurance (USA and Canada Only)	\$250,000 connected equipment insurance (USA / Canada only)
Optional coverage	3-5 year warranties, plus next day and on-site warranty coverage available for select opportunities. Contact Tripp Lite for additional information
SPECIAL FEATURES	
Cold Start	Yes, inverter can be "cold started" to enable temporary AC output during a power failure
Appearance	Attractive gray tower UPS

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/products/model.cfm?txtModelID=2800.