



NOTES:

1. LED includes integrated diode for reverse voltage protection.
2. LED includes integrated resistor for current limiting.

Operating Temperature Range	-30°C to +85°C
Storage Temperature Range	-40° to +100°C

TYPICAL ELECTRICAL & OPTICAL OPERATING CHARACTERISTICS

(Ta = 25 degree C)

PART NUMBER	EMITTING COLOR	AMPERAGE mA	VOLTAGE Vdc	LUMENS	DOMINANT WAVELENGTH	VIEWING ANGLE DEGREES
LE-0509-02R	RED	20mA	24.0	0.70	630nm	20
LE-0509-02Y	YELLOW	20mA	24.0	0.70	595nm	20
LE-0509-02G	GREEN	20mA	24.0	2.00	525nm	20
LE-0509-02B	BLUE	20mA	24.0	0.70	470nm	20
LE-0509-02W	WHITE	20mA	24.0	2.50	x = 0.28 y = 0.29	20
LE-0509-02WW	WARM WHITE	20mA	24.0	2.50	x = 0.401 y = 0.392	20

METRIC

THIRD ANGLE PROJECTION

DIMENSIONS ARE IN MILLIMETERS
TOLERANCE UNLESS OTHERWISE SPECIFIED
1 PL +/- 0.2
2 PL +/- 0.20
ANGLE +/- 0

JKL COMPONENTS CORPORATION

TITLE
T-3 1/4 24V WEDGE BASE LED

REV. NO.	DESCRIPTION/ECO NUMBER	APPV'D DATE	DRAWN BY	APPV'D BY DATE	SIZE	FSCM NO.	DRAWING NO.	RELEASED DATE	REVISION DATE	REV. NO.	SHEET				
B	CHANGE CHART	8/25/08	L. WENGSTROM	L.R. 8/25/08	A	55335	LE-0509-02	7/3/06	8/25/08	B	1 OF 1				
A	ADD LE-0509-02WW PART NO. TO LIST	12/7/07													
	ENGR RELEASE & CANCEL PL-0509-02-1 TO -5	7/3/06													
			- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED			SCALE	NONE	RELEASED DATE	7/3/06	REVISION DATE	8/25/08	REV. NO.	B	SHEET	1 OF 1