



BILL OF MATERIALS:

1. SSL-LX5093XX LED, TRIM TO 4mm.
2. SSI-LXR3816 HOLDER.
3. ANODE LEAD: LXP-WST24RDTOC, 24 AWG TINNED OVERCOAT, RED INSULATION, CUT 160mm LONG, STRIP 3mm & 9.5mm.
4. CATHODE LEAD: LXP-WST24BLTOC, 24 AWG TINNED OVERCOAT, BLACK INSULATION, CUT 160mm LONG, STRIP 3mm & 9.5mm.
5. SSH-LXH4815-BSG, BUSHING, INSERT & CRIMP.
6. CRIMP WIRE TO LED LEADS (2 PLACES).

RELIABILITY NOTE
OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



292 E. HELLEN ROAD
PALATINE, ILLINOIS 60067
(708) 359-2790

CONFIDENTIAL INFORMATION
THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX OPTO/COMPONENTS, INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX OPTO/COMPONENTS, INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

DATE: 11-7-96	DWN:	CHK'D:	APPD:
SCALE: N/A			

T-5mm LED PANEL INDICATOR, 6" LEADS