



JKL LAMP NUMBER	VOLTS RATED	AMPS ±10%	*MSCP ±25%	*LUMENS ±25%	AVERAGE LIFE HRS.	FILAMENT TYPE
6ESB	6.0	.040	.024	0.30	10,000	C-6V
10ESB	10.0	.040	.048	0.60	10,000	C-2V
12ESB	12.0	.040	.088	1.11	7,500	C-2F
24ESB	24.0	.040	.120	1.51	8,000	C-2F
28ESB	28.0	.040	.287	3.61	6,000	C-2F
48ESB	48.0	.040	.358	4.50	5,000	CC-2F

			<b>METRIC</b> DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0.1 ANGLE +/- 0		<b>JKL COMPONENTS CORPORATION</b>					
THIRD ANGLE PROJECTION			DRAWN BY: L. WENGSTROM APPV'D BY: QC DATE: 8/16/00		TITLE: T-2 TELEPHONE SLIDE BASE ANSI #5-23mol					
RELEASED			DATE: 8/16/00		SIZE: A	FSCM NO.: 55335	DRAWING NO.: SLIDE BASE ANSI #5-23mol			
REV. NO.			DESCRIPTION/ECO NUMBER		SCALE: NONE		RELEASED DATE: 8/16/00	REVISION DATE	REV. NO.	SHEET 1 OF 1
- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED										