


JKL LAMP NUMBER	VOLTS RATED	AMPS ±10%	MSCP ±25%	LUMENS ±25%	AVERAGE LIFE HRS.	FILAMENT TYPE
48	2.0	.060	.04	0.50	1,000	S-2
41	2.5	.500	.50	6.29	3,000	C-2R
40	6.3	.150	.52	6.54	3,000	C-2R
46	6.3	.250	.90	11.31	3,000	C-2R
1487	14.0	.200	1.40	17.60	3,000	C-2F
1821	28.0	.170	3.50	44.00	500	C-2F
1832	37.5	.050	.65	8.17	3,000	C-2F
RS22	130.0	.027	.60	7.54	5,000	C-5

METRIC



THIRD ANGLE PROJECTION

DIMENSIONS ARE IN MILLIMETERS

TOLERANCE UNLESS OTHERWISE SPECIFIED

1 PL +/- 0.2
2 PL +/- 0.20
ANGLE +/- 0

JKL

COMPONENTS CORPORATION

TITLE

T-3 1/4 MINIATURE SCREW BASE

REV. NO.	DESCRIPTION/ECO NUMBER	APPV'D DATE
A	CORRECTION ON RS22 RATINGS	2/21/01
	RELEASE	2/8/01

DRAWN BY	APPV'D BY	DATE
L. WENGSTROM	QC	2/21/01
- CAD DRAWING -		
MANUAL REVISIONS NOT PERMITTED		

SIZE	FSCM NO.	DRAWING NO.	SCREW BASE T-3 1/4		
A	55335		SCALE	RELEASED DATE	REVISION DATE
	NONE	2/8/01		2/21/01	REV. NO. A
					SHEET 1 OF 1