



NOTES:

1. GLASS ENVELOPE TO BE TIPLESS AND SEAMLESS.
2. BASE MATERIAL: BRASS, NICKEL PLATED.
3. LAMPS TO BE 100% AGED FOR EQUIVALENT OF TEN HOURS AT RATED VOLTAGE.
4. LAMPS TO BE DIESUNK WITH "JKL" AND NUMBER (EX: JKL 8270).
5. FINAL INSPECTION PER MIL. STD. 105D TO AN AQL OF 2.5 (NOTE: AS15 AND AS10 LAMPS WILL BE 100% INSPECTED FOR MSCP AND AMPERAGE).

JKL LAMP NUMBER	VOLTS RATED	AMPS ±10%	MSCP ±25%	LUMENS ±25%	AVERAGE LIFE HRS.	FILAMENT TYPE
8270	5.0	.115	.150	1.89	40,000	C-2R

<p>THIRD ANGLE PROJECTION</p>	<p>METRIC</p> <p>DIMENSIONS ARE IN MILLIMETERS</p> <p>TOLERANCE UNLESS OTHERWISE SPECIFIED</p> <p>1 PL +/- 0.2</p> <p>2 PL +/- 0</p> <p>ANGLE +/- 0</p>	<p>JKL COMPONENTS CORPORATION</p>							
	<p>DRAWN BY</p> <p>L. WENGSTROM</p>	<p>APPVD BY DATE</p> <p>BW 4/4/00</p>	<p>SIZE</p> <p>A</p>	<p>FSCM NO.</p> <p>55335</p>	<p>DRAWING NO.</p>	<p>FLANGE T-3/4</p>			
<p>RELEASE & CANCEL 7122, 8913, 6183, 8828</p>		<p>4/4/00</p>	<p>- CAD DRAWING -</p>		<p>SCALE</p> <p>NONE</p>	<p>RELEASED DATE</p> <p>4/4/00</p>	<p>REVISION DATE</p>	<p>REV. NO.</p>	<p>SHEET</p> <p>1 of 1</p>
<p>REV. NO.</p>	<p>DESCRIPTION/ECO NUMBER</p>	<p>APPVD DATE</p>	<p>MANUAL REVISIONS NOT PERMITTED</p>		<p>SCALE</p>	<p>RELEASED DATE</p>	<p>REVISION DATE</p>	<p>REV. NO.</p>	<p>SHEET</p>