



ELECTRO-OPTICAL CHARACTERISTICS (Tc=25°C)

PARAMETER	SYMBOL	MIN	TYP	MAX	TEST COND	UNITS
LASING WAVELENGTH	λ	655	658	660	Po=50mW	nm
THRESHOLD CURRENT	Ith		40	70	CW	mA
OPERATING CURRENT	Iop		125	150	Po=50mW	mA
OPERATING VOLTAGE	Vop		2.5	3.0	Po=50mW	V
SLOPE EFFICIENCY			0.7			W/A
MONITORING CURRENT	Im	0.05	0.5	2	Po=50mW	mA
BEAM DIVERGENCE:	θ	6	8	12	Po=50mW	deg.
	θ L	17	22	26	FWHM	deg.

ABSOLUTE MAXIMUM RATINGS (Tc=25°C)

PARAMETER	SYMBOL	MAX	UNITS
OPTICAL POWER	Pa	55	mW
LD REVERSE VOLTAGE	Vr(LD)	2	V
PD REVERSE VOLTAGE	Vr(PD)	30	V
OPERATING TEMP.	Top	- 10 TO + 40	°C
STORAGE TEMP.	Tstg	- 40 TO + 80	°C

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), XX=±0.5 (±0.020), XXX=±0.25 (±0.010), XXXX=±0.127 (±0.005), LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030), MIN.=^{+DECIMAL PRECISION}_{-0.00}, MAX.=^{+0.00}_{-DECIMAL PRECISION}

REV.	PART NUMBER OED-LDH66003E
660nm LASER DIODE, TO-18 PACKAGE, SUPER POWER, 50mW OUTPUT.	

CONFIDENTIAL INFORMATION
THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

RELIABILITY NOTE
OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.

290 E. HELEN ROAD
PALATINE, IL 60067-6976
PHONE: +1.847.359.2790
US WEB: www.lumex.com
TW WEB: www.lumex.com.tw

DRAWN BY: CT	CHECKED BY:	APPROVED BY:	DATE: 10.8.01 PAGE: 1 OF 1 SCALE: N/A
-----------------	-------------	--------------	---