

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION  
 © COPYRIGHT BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS			
P	LTR	DESCRIPTION	DATE	DWN	APVD
AD	00	B	OG3C-0255-03	21MAY03	TK MZ

SIDE VIEW  
(SEE NOTE 3)

SPECIFICATIONS:

LAMP DISSIPATION: 1.2W MAX.

INSULATION RESISTANCE: 100 MEGOHMS MIN.

DIELECTRIC STRENGTH: 2000 VAC.

OPERATING TEMPERATURE: -20°C TO +50°C  
(-4°F TO +122°F).

NOTES:

- LAMP IS T 3/4 MIDGET FLANGE BASE TYPE (LAMP NOT SUPPLIED).
- 164 IS NON-DILTIGHT SERIES, 165 IS DILTIGHT SERIES.
- VIEWS INCLUDE PLASTIC SHROUDS FOR AVAILABLE LENS SETS, (NOT SUPPLIED).

4 THE PLATINGS CONTAINED IN THIS PART SHALL CONTAIN NO LEAD.

5 PRELIMINARY PART, NOT RELEASED FOR PRODUCTION.

1571542-4	165TZ	4 5
1571542-3	164TZ	
1571542-2	164SZ	
1571542-1	164EZ	
5-1437569-9	165TZ	
5-1437569-3	165SZ	
4-1437569-6	165EZ	
4-1437569-1	164TZ	
3-1437569-2	164SZ	
1437569-8	164EZ	
TYCO PART No.	MODEL NUMBER	COMMENTS

REF AUGAT 81091

DIMENSIONS:		TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD		NAME	
INCHES		0 PLC ± -		W THIA 5-19-94		PILOT LIGHT	
		1 PLC ± -		W THIA 5-19-94		164/165 Z	
		2 PLC ± -		PRODUCT SPEC			
		3 PLC ± -		APPLICATION SPEC			
		4 PLC ± -		WEIGHT			
		ANGLES ± -		SCALE			
		FINISH		SHEET			
MATERIAL		FINISH		CUSTOMER DRAWING			

AMP 1471-9 REV 31MAR2000

H:\dmmod\

2-1437569-4

B

A