


REV	INITIALS	DATE	DESCRIPTION



NOTES:

1. TOLERANCE ±0.015 UNLESS NOTED OTHERWISE.
2. TOP CONDUCTIVE LAYER TO BE 0.007" THICK POLYESTER WITH A DIFFUSED SCRATCH RESISTANT COATING.
3. PIN ONE LOCATION IS THE UPPER MOST PIN WHEN VIEWING SCREEN WITH CABLE TO THE LEFT.
4. PINOUT TO BE AS INDICATED.
 PIN 1 - UPPER RIGHT,
 PIN 2 - LOWER RIGHT.,
 PIN 3 - SENSE,
 PIN 4 - UPPER LEFT,
 PIN 5 - LOWER LEFT.
5. FLEX TAIL IS TERMINATED USING AMP RECEPTACLE PIN 2-487406-4 WITH HOUSING 487378-4 OR EQUIVALENTS.
6. GLASS SUBSTRATE TO BE .074" THICK GLASS.
7. NOMINAL PANEL THICKNESS IS .087" ±.008.

BURQUEST TOUCH PRODUCTS			
301 WASHINGTON STREET CANNON FALLS, MN 55009			
TITLE: 15" DIAGONAL 5 WIRE TOUCHSCREEN			
DRN: MLR	DATE: 9/27/07	SCALE: 1:1	TOL: ±.015
CHKD:	DATE:	PART NUMBER:	DWG REV
APVD:	DATE:	400384	