

Fuseholder Open Design, Holder for MSF 125, horizontal, THT



125 VAC · 5 A (UL/CSA)

**Description**

- Through hole mounting
- Horizontal mount

Standards

- UL 512
- CSA C22.2 no. 39

Approvals

- UL File Number: E39328

References

General Product Information
Sicherungshalter zu MSF 125

Weblinks

Approvals, RoHS, CHINA-RoHS, e-Store, SCHURTER-Stock-Check,
Distributor-Stock-Check



Technical Data

| | |
|------------------------------|--------------------------------|
| Fuse-Link | Microfuse 125 V |
| Mounting | PCB |
| Terminal | Solder THT |
| Rated Voltage | 125 VAC |
| Rated Current | 5 A (UL/CSA) |
| Degree of Protection | IP 40 |
| Admissible Ambient Air Temp. | -40 °C to 85 °C |
| Climatic Category | 40/085/21 acc. to IEC 60068-1 |
| Material: Socket | Thermoplastic, black, UL 94V-0 |
| Material: Terminals | Silver-Plated Brass |
| Unit Weight (Socket/Cap) | 0.34 g |
| Storage Conditions | 0 °C to 60 °C, max. 70% r.h. |
| Product Marking | ☑, Approvals |

| | |
|------------------------------|---|
| Soldering Methods | Wave |
| Solderability | 235 °C / 2 sec acc. to IEC 60068-2-20, Test Ta, method 1 |
| Resistance to Soldering Heat | 260 °C / 10 sec acc. to IEC 60068-2-20, Test Tb, method 1A |
| Contact Resistance | < 5 mΩ at 20 mV |
| Dielectric Strength | > 3 kV between L-N (50 Hz; 1 min) |
| Impulse Withstand Voltage | > 4 kV between L-N |
| Insulation Resistance | > 10 MΩ between L-N (500 VDC; 1 min) |
| Overvoltage Category | I - III acc. to IEC 60664-1 |
| Pollution Degree | 1 - 3 acc. to IEC 60664-1 |

Dimensions

Length 11.3 mm

**Drilling Diagram****Variants**

| Holder | Order Number |
|--------|--------------|
| ● | 0031.7505 |

Distributor-Stock-Check | SCHURTER-Stock-Check | e-Store

Packaging Unit Plastic Bag (100 pcs.)