Fuse Clips with Mounting Holes For 1/4", 9/32", 13/32", and 9/16" Diameter Fuses

5000 Series

Dimensional Data











FIGURE 2

- Clips are made of a spring bronze of distinctly superior quality. This metal gives clips great gripping strength and ability to retain fuses under adverse conditions.
- Beryllium copper is by far the most satisfactory metal yet discovered for use in fuse clips. It has the ability to retain spring pressure better than any other metal under high current and high ambient conditions. It also has exceedingly high electrical conductivity.

1/4" DIAMETER FUSES

				Dimensions (Inches)					
Catalog	End	Clip		В (То	С	D	E	Hole	Fig.
Number	Stop	Mat.**	Finish	End Stop)	(Contact)	(Height)	(Width)	Dia.	Ref.
5681-01		BeCu	Silver						
5681-08	No	Spg. Br.	Nickel	t	.265	.410	.320	.132	2
5681-15		Spg. Br.	Bright Tin						
5682-01		BeCu	Silver	.014					
5682-02		BeCu	Silver						
5682-11	Yes	BeCu	Bright Tin	.130	.260	.410	.320	.132	1
5682-41		Spg. Br.	Bright Tin	.014					
5682-44		Spg. Br.	Bright Tin	.130					

13/32" DIAMETER FUSES

				Dimensions (Inches)					
Catalog	End	Clip		В (То	С	D	E	Hole	Fig.
Number	Stop	Mat.**	Finish	End Stop)	(Contact)	(Height)	(Width)	Dia.	Ref.
5956-16	No	Spg. Br.	Bright Tin	†	.307	.710	.470	.172	2
5960-07		BeCu	Silver	.168				.196	
5960-09		BeCu	Silver	.200				.172	
5960-44		Spg. Br.	Nickel	.200				.197	
5960-51		Spg. Br.	Bright Dip*	.168	.383	.710	.470	.196	1
5960-53	Yes	Spg. Br.	Bright Dip*	.200				.172	
5960-61		Spg. Br.	Bright Tin	.168				.196	
5960-62		Spg. Br.	Bright Tin	.168				.132	
5960-63		Spg. Br.	Bright Tin	.200				.172	
5960-64		Spr. Br.	Bright Tin	.200				.128	

9/32" DIAMETER FUSES

				Dimensions (inches)						
Catalog	End	Clip		В (То	С	D	E	Hole	Fig.	
Number	Stop	Mat.**	Finish	End Stop)	(Contact)	(Height)	(Width)	Dia.	Ref.	
5672-11	No	Spg. Br.	Bright Tin	t	.362	.520	.380	.172	2	
5674-01		BeCu	Silver							
5674-10	Yes	BeCu	Bright Tin	.168	.356	.520	.380	.172	1	
5674-41		Spg. Br.	Bright Tin							

- * Bright Dip is actually treated bare metal with no plating.
- ** Spg. Br. Spring Bronze; BeCu Beryllium Copper.
- † Hole in center of both clip and contact area.

9/16" DIAMETER FUSES

				Dimensions (Inches)						
Catalog	End	Clip		В (То	С	D	E	Hole	Fig.	
Number	Stop	Mat.**	Finish	End Stop)	(Contact)	(Height)	(Width)	Dia.	Ref.	
5591-42	Yes	Spg. Br.	Bright Dip*	250	F10	000	/00	170	1	
5591-52	103	Spg. Br.	Bright Tin	.250	.510	.890	.600	.172		
5592-01		BeCu	Silver					.200		
5592-11	No	Spg. Br.	Silver	t	.505	.875	.600	.172	2	
5592-33		Spg. Br.	Bright Dip					.172		

The only controlled copy of this Data Sheet is the electronic read-only version located on the Bussmann Network Drive. All other copies of this Data Sheet are by definition uncontrolled. This bulletin is intended to clearly present comprehensive product data and provide technical information that will help the end user with design applications. Bussmann reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Bussmann also reserves the right to change or update, without notice, any technical information contained in this bulletin. Once a product has been selected, it should be tested by the user in all possible applications.

