

Surface Mount Fuse, 3.2 x 1.55 mm, Super-Quick-Acting FF, 125 VAC, 125 VDC, 150 °C



UL 248-14 · 125 VAC · 125 VDC · Super-Quick-Acting FF

**Description**

- Max. ambient temperature 150 °C
- Hermetically sealed and robust construction
- Thin-film technology

**Standards**

- UL 248-14
- CSA C22.2 no. 248.14

**Approvals**

- UL File Number: E41599

**Applications**

- Medical equipments
- Military

**References**

[General Product Information](#)  
Time-Current Curves see last page  
[Packaging Details](#)

**Weblinks**

[Approvals](#), [RoHS](#), [CHINA-RoHS](#), [e-Store](#), [SCHURTER-Stock-Check](#),  
[Distributor-Stock-Check](#)



**Technical Data**

Rated Voltage	32 - 125 VAC, 125 VDC
Rated Current	0.2 - 5 A
Breaking Capacity	50 A
Characteristic	Super-Quick-Acting FF
Mounting	PCB, SMT
Admissible Ambient Air Temp.	-55 °C to 150 °C
Climatic Category	55/150/21 acc. to IEC 60068-1
Material: Housing	Ceramic
Material: Terminals	Tin-Plated Nickel
Unit Weight	0.03 g
Storage Conditions	0 °C to 60 °C, max. 70% r.h.
Product Marking	none

Soldering Methods	Reflow, Wave
Solderability	245 °C / 3 sec acc. to IEC 60068-2-58, Test Td
Resistance to Soldering Heat	260 +0/-5 °C / 30 sec acc. to IPC/JEDEC J-STD-020D, Level 1
Life Test	MIL-STD-202, Method 108A (1000h @ 0.70*In @ 70°C)
Load Humidity Test	MIL-STD-202, Method 103B (1000h @ 0.1*In @ 0.85 r.H. @ 85°C)
Moisture Resistance Test	MIL-STD-202, Method 106E (50 cycles in a temp./mister chamber)
Terminal Strength	MIL-STD-202, Method 211A (Deflection of board 1 mm for 1 minute)
Thermal Shock	MIL-STD-202, Method 107D (200 air-to-air cycles from -55 to +125°C)
Resistance to Solvents	MIL-STD-202, Method 215A
Flammability	min. UL 94V-1 (acc. to EIA/IS-722, Test 4.12)

**Dimensions**

Length 3.2 mm



Solder pads


## Pre-Arcing Time

Rated Current  $I_n$     1.0 x  $I_n$  min.    2.5 x  $I_n$  max.

0.2 A - 5 A                      4 h                      5 s

## Variants

Distributor-Stock-Check | SCHURTER-Stock-Check | e-Store

Rated Current [A]	Rated Voltage [VAC]	Rated Voltage [VDC]	Breaking Capacity	Voltage Drop 1.0 $I_n$ typ. [mV]	Cold Resistance typ. [ $m\Omega$ ]	Melting $I^2t$ 4.0 $I_n$ typ. [ $A^2s$ ]			Order Number
0.2	125	125	1)	258	1020	0.0008	●	●	3410.0021.xx
0.25	125	125	1)	250	800	0.0009	●	●	3410.0022.xx
0.375	125	125	1)	165	361	0.0037	●	●	3410.0025.xx
0.5	125	125	1)	150	247	0.0042	●	●	3410.0027.xx
0.75	125	125	1)	100	115	0.01	●	●	3410.0029.xx
1	125	125	1)	124	98.7	0.035	●	●	3410.0031.xx
1.5	125	125	1)	105	56	0.064	●	●	3410.0033.xx
2	125	125	1)	98	39	0.089	●	●	3410.0035.xx
2.5	125	125	1)	90	29.5	0.15	●	●	3410.0036.xx
3	125	125	1)	88	24.1	0.18	●	●	3410.0037.xx
4	63	125	2)	83.5	17	0.23	●	●	3410.0240.xx
5	32	125	3)	90	13.5	0.45	●	●	3410.0141.xx

1) 50 A @ 125 VAC / 300 A @ 125 VDC

2) 50 A @ 63 VAC / 50 A @ 125 VDC / 300 A @ 32 VDC

3) 50 A @ 32 VAC / 50 A @ 125 VDC / 300 A @ 32 VDC

## Packaging Unit

- .xx = .01 Blister Tape (100 pcs.)
- .xx = .02 Blister Tape 18 cm Reel (750 pcs.)
- .xx = .03 Blister Tape 33 cm Reel (3000 pcs.)
- .xx = .04 Blister Tape 33 cm Reel (10000 pcs.)

## Time-Current Curves

