


Part Number: MS22 20005

Ordering Different Lead Types:

Inside Kinked Leads	Use -A after Ametherm's part #
Outside Kinked Leads	Use -B after Ametherm's part #

For example: to order an inside kinked lead use part number MS22 20005-A



Electrical Specifications:

Resistance @ 25°C	20.0 Ω \pm 25%
Max Steady State Current Up to 65°C	5.0 A
Max Recommended Energy Rating (Joules)	180.0 J
Actual Failure Point of Instantaneous Energy (Joules)	360.0 J
Resistance @ 100% of Max Current	0.190 Ω
Resistance @ 50% of Max Current	0.485 Ω
Body Temperature @ 100% Current Rating	170 °C
Dissipation Constant	42.5mW/°C
Thermal Time Constant	114 seconds
Material Type	"H"
Max Recommended Capacitance @ 120VAC/240VAC/440VAC	12000 μ F/ 3000 μ F/ 900 μ F
Max Recommended Voltage	600 Vrms with 420 μ F

Mechanical Specifications:

D	20.0 \pm 1.0 mm
T	5.0 \pm 0.2 mm
Lead Diameter	1.0 \pm 0.1 mm
S	7.8 \pm 2.0 mm
L	38.0 \pm 9.0 mm
Straight Leads Coating Run Down	5.0 \pm 1.0 mm
B	9.35 \pm 0.85 mm
C	3.82 \pm 1.0 mm

Revision Date: March 19, 2003

Ametherm, Inc. 3111 N. Deer Run Road #4 Carson City, NV 89701
 Telephone: (800) 808-2434 (775) 884-2434 Fax: (775) 884-0670

www.ametherm.com