

Part Number: MS22 50004

**Ordering Different Lead Types:**

Inside Kinked Leads	Use <b>-A</b> after Ametherm's part #
Outside Kinked Leads	Use <b>-B</b> after Ametherm's part #

For example: to order an inside kinked lead use part number MS22 50004-A



**Electrical Specifications:**

Resistance @ 25°C	50.0 Ω ± 25%
Max Steady State Current Up to 65°C	4.0 A
Max Recommended Energy Rating (Joules)	240.0 J
Actual Failure Point of Instantaneous Energy (Joules)	430.0 J
Resistance @ 100% of Max Current	0.360 Ω
Resistance @ 50% of Max Current	0.790 Ω
Body Temperature @ 100% Current Rating	159 °C
Dissipation Constant	47.8 mW/°C
Thermal Time Constant	119 seconds
Material Type	"H"
Max Recommended Capacitance @ 265Vrms/440VAC	3400µF/1200µF

**Mechanical Specifications:**

D	20.0 ± 1.0 mm
T	7.0 ± 0.7 mm
Lead Diameter	1.0 ± 0.1 mm
S	7.8 ± 2.0 mm
L	38.0 ± 9.0 mm
Straight Leads Coating Run Down	5.0 ± 1.0 mm
B	9.2 ± 0.85 mm
C	3.82 ± 1.0 mm

Revision Date: March 19, 2003

**Ametherm, Inc.** 3111 N. Deer Run Road #4 Carson City, NV 89701  
 Telephone: (800) 808-2434 (775) 884-2434 Fax: (775) 884-0670

[www.ametherm.com](http://www.ametherm.com)