

Part Number: SL12 25002

### Ordering Different Lead Types:

Inside Kinked Leads	Use <b>-A</b> after Ametherm's part #
Outside Kinked Leads	Use <b>-B</b> after Ametherm's part #

For example: to order an inside kinked lead use part number SL12 25002-A



### Electrical Specifications:

Resistance @ 25°C	25.0 $\Omega$ $\pm$ 20%
Max Steady State Current Up to 65°C	2.0 A
Max Recommended Energy Rating (Joules)	30.0 J
Actual Failure Point of Instantaneous Energy (Joules)	60.0 J
Resistance @ 100% of Max Current	0.546 $\Omega$
Resistance @ 50% of Max Current	0.933 $\Omega$
Body Temperature @ 100% Current Rating	142 °C
Dissipation Constant	12.7mW/°C
Thermal Time Constant	40 seconds
Material Type	"H"
Max Recommended Capacitance @ 120VAC/240VAC	2000 $\mu$ F/ 500 $\mu$ F

### Mechanical Specifications:

D	12.0 $\pm$ 0.5 mm
T	5.1 $\pm$ 0.2 mm
Lead Diameter	0.8 $\pm$ 0.1 mm
S	7.8 $\pm$ 2.0 mm
L	38.0 $\pm$ 9.0 mm
Straight Leads Coating Run Down	5.0 $\pm$ 1.0 mm
B	6.35 $\pm$ 0.60 mm
C	3.42 $\pm$ 0.5 mm