

Home> Products > Thermostats > 3455RC > Product Page

## 3455RC 01000235

 Order Product and Get Support

- U.S. Authorized Distributors
- Global Sales & Service
- N. American Sales Reps
- Distributor Inventory
- Technical Assistance
- White Papers
- Literature Request
- Test and Measurement Catalog
- RoHS Product List
- Customer Feedback



Actual product appearance may vary.

## Features

table> Description

Cost effective Rivet sleeve construction High profile High temperature High current

## **Potential Applications**

3455RC Redi-Temp Series Ceramic

Automatic Reset Thermostats

Copy machines Power supplies Telecommunications Office copy machines Ovens

Shipped from stock, the 3455RC Series thermostats are often suitable for applications such as copy machines, power supplies, telecommunications and ovens. UL, CSA and European approval agencies listings available.

## **Supporting Documentation**

None Available

Product Specifications	
Functional Properties	Open on rise
Reset Type	Automatic
Amperage	15 A/10 A resistive max.
Voltage	120 Vac/240 Vac
Operating Temperature	0 °C to 260 °C [32 °F to 500 °F]
Environmental Exposure Range	-20 °C to 287 °C [0 °F to 550 °F]
Open Temperature	101.7 °C [215 °F]
Close Temperature	85.0 °C [185 °F]
Open Tolerance	3.3 °C [6 °F]
Close Tolerance	4.4 °C [8 °F]
Dielectric Strength	MIL-STD-202, Method 301; 2000 Vac 60 Hz - Terminal to Case
Insulation Resistance	MIL-STD-202, Method 302; 500 MOhm

Contact Resistance	MIL-STD-202, Method 307; 0.050 Ohm max.
Housing Material	Ceramic
Contact Material	Silver/nickel alloy
Agency Approvals and Standards	UL, CSA, VDE
Mounting	B203S moveable bracket
Series Name	3455RC

My Links

- Login to iCOM
- Login as Rep/AD
- Login as Guest
- Login to Digital University

**Keyword Search** 

Search for product and support information.

All Sensing and Contrc

**Product Search** 

Part number search:

Use (\*) to expand search

Specification Search

Terms & Conditions | Privacy Statement | Site Map

Ð

Ð