

## Honeywell Sensing and Control



Home > Products > Conductive Plastic Potentiometers > 381 > Product Page

### 381NS1MEG



Actual product appearance may vary.

**381 Series Industrial Potentiometer,  
Conductive Plastic Element, Solder lug  
Terminals, 1 W Power Rating, 1 MOhm  
Resistance Value**

#### Features

Conductive plastic element  
Linear taper  
Rugged construction: Metal case and nickel-plated brass shaft and bushings  
Solder lug terminals  
Rotary switch, SPST, CCW detent, open in detent

#### Potential Applications

Manual controls  
Welding and heating  
Telecommunications

#### Description

The 381 Series is a 1 watt potentiometer with a conductive plastic element and a metal housing.

#### Supporting Documentation

[▶ Dimensions](#)

[▶ Accessory: Knobs](#)

Product Specifications	
Potentiometer Type	Industrial
Element Type	Conductive Plastic
Terminal	Solder lug
Power Rating	1 W
Resistance Value	1 MOhm
Resistance Tolerance	± 20 %
Linearity	± 5 %
Bushing Thread	6,35 mm [0.25 in] x 32 NEF-2A
Bushing Length	6,35 mm [0.25 in]
Bushing Type	Standard
Shaft Diameter	3,18 mm [0.125 in]
Shaft Length	19,05 mm [0.75 in]
Shaft Ending	Slotted
Body	15,88 mm [0.625 in] diameter, ± 0,79 mm [0.031 in]
Electrical Taper	Linear

#### My Links

- [Login to iCOM](#)
- [Login as Rep/AD](#)
- [Login as Guest](#)
- [Login to Digital University](#)

#### Keyword Search

Search for product and support information.

 

#### Product Search

Part number search:

   
 Use (\*) to expand search

→ [Specification Search](#)

Operating Temperature	-40 °C to 120 °C [-40 °F to 248 °F]
Working Voltage (Max.)	350 V
Rotational Life	25000 cycles
Mechanical Rotation	300°
Availability	Global
Series Name	381
UNSPSC Code	4111363300
UNSPSC Commodity	4111363300 Potentiometers

[Terms & Conditions](#) | [Privacy Statement](#) | [Site Map](#)