

NMX-750, Power Factor Corrected Multiple Output, Forced Current Sharing



SPECIFICATIONS:

INPUT

Ac Input: 90-264 Vac continuous range, 47 to 63 Hz. Internally fused for 15 A.

Power Factor: 0.99 typical at full load. Meets EN61000-3-2 Class A.

Inrush: Cold start ac current is less than 65 A at 115 Vac and 130 A at 230 Vac. Limited by thermistor.

Brownout Protection: Holds regulation to 85 Vac.

Holdup Time: 20 ms minimum after removal of power at full load.

Efficiency: 75% typical.

Ac Power Fail: Provides TTL "0" 5 ms before output voltage goes out of regulation band upon loss of ac power.

OUTPUT

Adjustability: Outputs #1 and 2 user adjustable $\pm 5\%$ minimum. Output #3 tracks #2; initial accuracy $\pm 4\%$. Output #4 user adjustable $\pm 5\%$ minimum, or $+5\%$ only if voltage is 5.2 V.

Line & Load Reg: Outputs #1, 2, and 4 hold $\pm 1\%$ over ac input range and 0 to 100% load change. Output #3 requires 20% minimum load on outputs #2 and 3 to hold $\pm 4\%$.

Ripple & Noise: Less than 1% p-p or 100 mV, whichever is greater.

Remote Sense (Outputs #1 and 2): Compensates for 250 mV total line drop. Open sense lead protection. (See Redundancy.)

Temperature Coefficient (Outputs #1, 2, and 4): 0.02% per degree C.

Stability: 0.1% over 8 hours after 30 minutes warm-up.

Transient Response (Outputs #1, 2, and 4): Output voltage returns to within 1% in less than 500 μ s for a 50% load change. Peak transient does not exceed 5%.

Overload Protection: All outputs are protected against overload and short circuit. Automatic recovery upon removal of fault.

Overvoltage Protection (Outputs #1 and 2): Protects load against power supply induced over voltage. Trip point is factory set so that output voltage cannot exceed 136% of nominal.

Peak Output Current: Dual current ratings define continuous and peak currents. The peak current shown can be delivered for a maximum period of 30 seconds.

Remote Inhibit: Contact closure to the negative sense line or a TTL level "0" turns off dc outputs.

Dc Power Good: Provides a TTL "1" when output #1 is above 4.6 V nominal.

FEATURES:

- Forced current sharing for N + 1 redundancy
- Remote sense on outputs #1 and 2
- Universal ac input
- 0.99 typical power factor
- Dual converter design eliminates interaction between logic and auxiliary outputs
- Low ripple and noise on all outputs
- Dc power good and ac power fail signals
- True remote inhibit
- Monotonic turn-on and turn-off

Redundancy: External OR-ing diodes and forced current sharing on output #1 provide "N+1" capability. Remote Sense (+S) compensates for additional 0.6 V diode voltage drop. When the current sharing terminal is connected between units, current sharing remains within 10% of the unit's full output current rating. Requires minimum load of 12.5 A on +5V.

ENVIRONMENTAL

Thermal Protection: Shuts down power supply if overheated. Automatic recovery.

Temperature Range: 0° to 50° C at full ratings.

Safety Agencies: Most models are approved to UL1950; CSA 22.2 #234; IEC 950 and TÜV EN60950, Class 1 SELV., CE 72/23/EEC/93/68EEC (low voltage directive).

Conducted RFI: Meets FCC Part 15, Class A; EN55022 Class A.

Output Isolation: Isolated from ground 50 Vdc.

Reverse Voltage: Protected against reverse voltage up to supply current rating.

Cooling: Self cooled with internal ball-bearing fans.

OPTIONS:

Option "B", Barrier Strip: Provides auxiliary output connections on #6-32 terminal screws with 3/8" centers.

AC INPUT(90-264 VAC Continuous Range)

FUNCTION	115 VAC	230 VAC	CONNECTOR
TB1-(L)	Line	Line 1	Barrier strip
TB1-(N)	Neutral	Line 2	#6-32 screws, 3/8" centers
TB1-(GND)	Safety Ground	Safety Ground	

DC OUTPUT

FUNCTION	LOCATION	NOTES	CONNECTOR
Output #1	Terminal marked +V	Main output	Bus bars
	Terminal marked -V	Rtn (common)	#1/4-20 screws
Output #2	J6-3, 11, 4, 12	Rtn (common)	AMP#770974-1 mates
	J6-5, 13, 6, 14, 7, 15		with connector 770583-1
Output #3	J6-8, 16	Rtn (common)	with sockets #171639-1
	J6-5, 13, 6, 14, 7, 15		(AWG #20 to #16)
Output #4	J6-1, 9	(+) Floating Output	
	J6-2, 10	(-) Floating Output	

STATUS AND CONTROL

FUNCTION	LOCATION	NOTES	CONNECTOR
Remote Sense	J1-5	Output #1 Sense	AMP MTA type
	J1-4	Output #1 Sense Rtn	#640456-5 pin
DC Power Good	J1-3	Reference to common	header (locking)
	J1-2	when #1 Sense Rtn is	
Current Share	J1-1	Terminated	
Remote Sense	J3-1	Output #2 Sense	AMP MTA type
	J1-4	Output #2 Sense Rtn	#640456-4 pin
Ac Power Fail	J3-3	Reference to common	header (locking)

