



**Features:**

- N.A. AC input
- Fully enclosed plastic case
- Fully regulated output
- High Efficiency
- Warranty: 5 years

**Environmental**

- Operating temperature....0° C to 40° C
- Storage temperature.....-55° C to 85° C
- Weight: 0.5 lbs

**EMI**

Meets FCC class B

**Safety**

UL 1950  
cUL Listed to CSA 22.2 No. 950

**Electrical specifications**

**Input**

- Voltage.....90-132VAC
- Current.....0.75A
- Frequency.....47-63 Hz
- Input connector.....2 Pin NEMA 5/15 plug

**Output**

- Line regulation.....TYP 1%
- Load regulation.....5% Max
- Set point..... 5% of rated output
- Hold up time.....12 ms min. at full load 115 V

- Over voltage protection.....Built-in
- Over current protection.....Built-in
- Short circuit protection.....Pulsing Mode, auto recovery
- Ripple/noise(Vp-p).....1%
- Output connector.....barrel type(5.5 x 2.5 x 9.5mm)



**Output Electrical Specifications**

| Model No.  | Voltage | Power | Current |
|------------|---------|-------|---------|
| WP1205-760 | 5       | 12    | 2.4A    |
| WP1215-760 | 15      | 12    | 0.8A    |
| WP1212-760 | 12      | 12    | 1A      |
| WP1224-760 | 24      | 12    | 0.5A    |

