



Features:

- Wide Range AC input
- Fully enclosed plastic case
- Fully regulated output
- High Efficiency
- Warranty: 5 years

Environmental

- Operating temperature....0° C to 40° C
- Storage temperature.....-55° C to 85° C
- Weight: 2.5 lbs

EMI

Meets FCC class B, CISPR 22 class B

Safety

- UL 1950
- CSA 950
- CE mark

Polarity:

Pin1	Pin2	Pin3	Pin4	Pin5
Com	Com	V+	Com	V+

Electrical specifications

Input

- Voltage.....100-240VAC(90-265)
- Current.....1A @ 115VAC
- Frequency.....47-63 Hz
- A/C cord.....Included - 6 foot cord
- Input connector.....3 Pin IEC 320 receptacle

Output

- Line regulation.....TYP 1%
- Load regulation..... 5% Max
- Set point..... +/-3% at 60% load
- Hold up time.....20 ms min. at full load 115 VAC
- Over voltage protection.....Built-in
- Over current protection.....Built-in
- Short circuit protection.....Pulsing Mode, auto recovery
- Ripple/noise(Vp-p).....1%
- Output connector.....D5(5 PIN DIN)

Output Electrical Specifications

Model No.	Voltage	Power	Current
W7215-D5	15	72	4.8A
W7218-D5	18	72	4A
W7224-D5	24	72	3A
W7248-D5	48	72	1.5A

