


Input

Rated input voltage	100 V- 240 V ac
Input voltage range	90 V to 264 V ac
Rated frequency	50-60 Hz
Frequency range	47-63 Hz
Rated input current	400 mA RMS max.
Inrush current	30A max (at 260 V ac input, full load)

Output

Output voltage	24 Vdc at 0.4 A
Output min. current	0A
Short circuit protection	output shut down and auto restart
Ripple voltage	240 mV (p-p) (with a 0.1 μ F ceramic capacitor and a 10 μ F electrolytic capacitor to output at 20 MHz bandwidth)
Efficiency	75% typ. (at 100 V ac/50 Hz or 240 V ac/50 Hz input, full load)

Safety and EMI

Safety approvals	UL/cUL, CE, TUV/GS
RoHS compliant	yes

Environmental

Storage temperature	-20°C ~ +85° C
Operating temperature	0°C ~ +40° C



CUI INC

Part No: DMS240040-P5-IC

Description: switching power supply
w/ interchangeable input blades

Date: 9/25/2006

Unit: mm

Page No: 2 of 3

Label




CUI INC



POWER ADAPTOR

P/N : DMS240040-P5-IC

INPUT : 100-240V~ 0.4A 47-63Hz

OUTPUT : 24V  0.4A



99BJ
E176177
I.T.E.
POWER
SUPPLY



indoor
use only

RoHS TR10R240 MADE IN TAIWAN

Mechanical Drawing
