

DEVICE COUNT
XELTEK SUPERPRO Now
Supports over
25,715 Devices
Click here to see the
complete device list

HOME

DOWNLOAD

SUPPORT

DISTRIBUTORS

RESOURCE

Product Search:

Go

[Advanced search](#)

Products

- ❖ SuperPro 3000U
- ❖ SuperPro 3000U-100
- ❖ SuperPro 3000U Cluster
- ❖ SuperPro 580U
- ❖ SuperPro 280U
- ❖ SuperPro LX
- ❖ SuperPro Z
- ❖ SuperPro 9000U
- ❖ Legacy Products
- ❖ Socket Adapters
- ❖ EPROM Erasers

Applications

- ❖ Programmer Comparison
- ❖ PIC Programming
- ❖ Flash Programming
- ❖ Nand Flash Programming
- ❖ EPROM Programming
- ❖ In-System Programming
- ❖ Gang Programming
- ❖ High Volume Production
- ❖ BGA Adapters

SuperPro 9000U Gang Programmer #16141



SuperPro-9000U

USB Interfaced Ultra-F programming modules Programmer

- ❖ Device List
- ❖ Software Downloads
- ❖ Product Manual
- ❖ Warranty Support
- ❖ Optional Products

[View detailed image:](#)

Features:

- 4ea high speed 48pin DIP programming sockets
 - Supports **20,781** devices and growing, more than any gang programmer in the market.
 - 430+ socket adapters including 150+ FBGA package types supported
 - Operates in both PC and stand-alone mode without a PC for volume production
 - Asynchronous fast programming. Each module is independent of one another.
 - Programming starts automatically when a chip is inserted
 - High speed programming (give examples here)
 - ISP (In-System Programmable) devices supported
 - No experienced operator with the knowledge of PC or V is necessary
- [more detailed feature information](#)

Device Updates:

- XELTEK also adds devices upon customer's request at its option.
- We update new devices onto Superpro3000U regularly and also upon request. Device update is free of charge during the warranty period of programmer purchased. We do not have free device update service for other programmers. If you are interested in the new device update service, please purchase Superpro3000U programmer.

Warranty Support:

- Programmer is warranted to be free of manufacturing or workmanship defects for one year from the date of purchase.
- Online Technical Support is also available 24 hours or you may call us during business hours through Friday 8:30am to 5:30pm (PST).

Hardware & Electrical Specifications:

- Supported devices: EPROM, EEPROM, Serial EPROM, Paged EPROM, Serial Flash EPROM (NOR and NAND), NONVRAM, SPLD, CPLD, EPLD, Firmware Microcontroller, SRAM and Standard logical device. With voltages down to 1.8V.
- Packages supported: DIP, SDIP, PLCC, JLCC, SOIC, QFP, TQFP, PQFP, VCC, TSOPII, SOP, PSOP, TSSOP, SON, EBGA, FBGA, VFBGA, UBGA, CSP, SCSP
- PC interface: USB
- Stand-alone Interface: 16 Character by 4 line back-lighted LCD, 6 standard Compact Flash cards (removable, 64MB as standard which can support up to 2GB devices, necessary for both PC mode and stand-alone mode)
- Standard Package includes: Programmer main unit, external power supply, USB cable, User's Guide, software CD.
- Optional accessories: Package adapters
- Electrical spec. of the AC adapter: AC input 90V to 250V, 50/60Hz, DC output 5V
- Mechanical parameter: Main unit: Size: 540*195*58mm Weight: 3.1Kg
Power supply: Size: 608*360*150mm Weight: 8.5Kg

Optional Products

Compact Flash Card 64MB	Price: \$29.00	Add to cart
Compact Flash Card 128MB	Price: \$70.00	Add to cart
Compact Flash Card 64MB 4 Packs	Price: \$100.00	Add to cart
Compact Flash Card 128MB 4 Packs	Price: \$150.00	Add to cart

Ordering Information

Weight 24.00 lbs
Price: \$3,495.00

Quantity

If you see this message it means that your browser doesn't support Javascript or JavaScript is disabled. Please enable JavaScript in your browser settings for the proper functionality of Xeltek.com.

[Contact Us](#) | [Home](#) | [Download](#) | [Support](#) | [Distributors](#) | [Resource](#)

[Terms & Conditions](#) | [Privacy statement](#) | [Restrictions & Compliance](#)

Copyright © 2006 Xeltek Inc.