# CARD-D-PULLS™

# **Printed Circuit Board Inserters/Extractors**

- Select from 14 standard stock styles for  $\frac{1}{16}$ ,  $\frac{3}{2}$  and  $\frac{1}{2}$  PCBs.
- Strong and rigid with optimum leverages to assist in both insertion and extraction
- Directly interchangeable with competitive styles; widest selection of standards
- Large areas for hot stamping
- Special colors available

\_Ø.025 [Ø0.6mm] <u>\_</u>

1209 Series Inserter/Extracto

### **Material Specifications:**

1209 series: 6/6 Nylon per ASTM D4066 PA111, UL Rated 94V-2

# Oxygen Rating Index:

Over 28%

Color: Natural (Off White) or Black

Part No.	S	PCB	DESC
1209-062	.075 (1.9)	.062 (1.6)	83023-19W
1209-093	.100 (2.5)	.093 (2.4)	83023-20W
1209-125	.140 (3.6)	.125 (3.2)	83023-21W

#### Furnished with Spring Pins RP-375

### Standard Drawing Tolerances:

(unless oth	erwise indicated)
Fractions:	± 1/64 (0.4)
.X =	±0.10 (2.5)
.XX =	± 0.01 (0.25)
.XXX =	± 0.005 (0.13)

Note: Passivated Stainless Steel Spring Pins per MIL-P-10971 furnished with each Ejector or Inserter/Extractor.



## **Spring Pin**

Part No.	L	D
RP-250	1/4 (6.4)	3/32 (2.4)
RP-312	5/16 (8.0)	3/32 (2.4)
RP-375	3/8 (9.5)	1/8 (3.2)





