

# Subracks Introduction



## Euro Packaging DIN Metric Subracks IEC 297-1 and ANSI/EIA 310D (1992)

VectorPak™ DIN-based Metric Subracks are designed in accordance with DIN 41914 specifications are available in standard 19" or smaller widths. Glass-filled Noryl card guides provide rigidity and lock in securely, yet can be removed without special tools. Card guide mounting holes are positioned at each 0.2" Horizontal Position ('HP'). These racks available for 3U, 6U or 9U wide cards and up to 400MM L and non-standard/custom sizes are available by contacting the factory.



DIN  
Subracks

These racks will support 1.6 MM (0.062") thick PCB's with the following dimensions:

### Standard EuroCard Heights

3U	100.00 MM	(3.937")
6U	233.35 MM	(9.187")
9U	366.70 MM	(14.437")

### Standard Eurocard Depths

160 MM	(6.299")
220 MM	(8.661")
280 MM	(11.024")
340 MM	(13.386")
400 MM	(15.499")



Vector DIN Subracks can accommodate VME/DIN Backplanes and can be configured in a combination of 6U and 3U cards in a single subrack.

Other features include:

- Brushed aluminum construction with clear irridite finish.
- Available fully assembled or flat-packed kit.
- Card guides sold separately.
- DIN 41612 connector compatibility with installation of AS1/2 adapter plates.



CCK Card Cage Kit



P/N CG1-160 160mm card guide