



$.125^{+.003}_{-.001}$ (3.18 $^{+0.08}_{-0.03}$)
DIA.



$.218^{+.003}_{-.001}$
(5.54 $^{+0.08}_{-0.03}$)



TYPICAL MOUNTING HOLES
PANEL THICKNESS: .048-.085 (1.2-2.2)

NOTES:

- MAT'L: NYLON 6/6 (RMS-48).
FLAME RETARDANT, NYLON (RMS-19),
AVAILABLE BY SPECIAL ORDER ONLY.
- COLOR: NATURAL.

| PART NO. | "L" ±.030 (±0.8) | "A" ±.024 (±0.6) | "B" ±.016 (±0.4) |
|----------|---------------------|---------------------|---------------------|
| RN-250-2 | 2.5 (63.5) | 2.0 (50.8) | - |
| RN-300-2 | 3.0 (76.2) | 2.5 (63.5) | - |
| RN-350-2 | 3.5 (88.9) | 3.0 (76.2) | - |
| RN-400-2 | 4.0 (101.6) | 3.5 (88.9) | - |
| RN-450-2 | 4.5 (114.3) | 4.0 (101.6) | - |
| RN-500-2 | 5.0 (127.0) | 4.5 (114.3) | - |
| RN-550-2 | 5.5 (139.7) | 5.0 (127.0) | - |
| RN-600-2 | 6.0 (152.4) | 5.5 (139.7) | - |
| RN-650-2 | 6.5 (164.1) | 6.0 (152.4) | - |
| RN-700-2 | 7.0 (177.8) | 6.5 (164.1) | - |
| RN-700-3 | 7.0 (177.8) | 6.5 (164.1) | 3.25 (82.2) |
| RN-750-2 | 7.5 (190.5) | 7.0 (177.8) | - |
| RN-750-3 | 7.5 (190.5) | 7.0 (177.8) | 3.5 (88.5) |
| RN-800-2 | 8.0 (203.2) | 7.5 (190.5) | - |
| RN-800-3 | 8.0 (203.2) | 7.5 (190.5) | 3.75 (94.9) |
| RN-850-2 | 8.5 (215.5) | 8.0 (203.2) | - |
| RN-850-3 | 8.5 (215.5) | 8.0 (203.2) | 4.0 (101.6) |

| | | |
|-----|---|-------------|
| A | ADDED FLAME RET. TO NOTES; CHANGED FILE NO. | SM 02.21.02 |
| REV | DESCRIPTION | ENGR DATE |

| | | | | | | | | | |
|---|--|------------------|--|---------------|-----------|-------|------------|------------|--|
| TITLE: NARROW CARD GUIDE (RN) | | | | DWG IN IN(mm) | | FINAL | | PRINT TYPE | |
| TOLERANCES UNLESS NOTED .XX=±.010 .XXX=±.005 FRAC=±1/64 ANG=±1° | | FILE # RN | DWN: J.B. | APP: | PART # | | PRINT TYPE | | |
| | | MAT'L: SEE NOTES | DT: 04-08-97 | DT: | SEE CHART | | CA | | |
| | | RE: RICHCO, INC. | RICHCO INC. PO BOX 804238, CHICAGO, 60680 (773) 539-4060 | | | | | | |