

SI-300CC Camera Controller

Product Overview

Multi-Camera Control The TDK RF Solutions SI-300CC Camera Controller is capable of controlling up to four independent camera units. It allows precision manipulation of camera features such as pan, tilt, zoom, and focus with the use of two joysticks. In addition, the SI-300CC comes fully equipped with a graphical LCD, four function keys, four special keys, and twelve numerical keys for user-friendly control.

Flexibility The SI-300CC can be operated manually or through an IEEE 488 interface. The camera controller can be rack mounted or used as a stand-alone unit.

Audio Monitoring The SI-300CC can also be utilized for audio monitoring when used with a TDK VC-04 video camera optioned with an internal microphone.

Signal Conversion The controller contains up to four fiber optic video receivers, which convert the fiber optic video signal to a standard 75 ohm analog video signal for use in standard video equipment.

Applications

- EUT monitoring
- Shielded chamber monitoring
- Multiple camera manipulation



The TDK RF Solutions SI-300CC Camera Controller can control up to four remote video cameras. Manipulation of camera features such as pan, tilt, zoom, and focus can be accomplished via user-friendly joysticks or built-in function keys.

System Features

- Capable of controlling up to four remote video camera units using fiber optic interfaces
- Camera control features pan, tilt, zoom, focus, iris control
- Graphical 240 x 64 LCD display
- Keyboard control with four function keys
- Easy to operate ergonomic controls
- GPIB control for front panel functions
- Built-in fiber optic video receiver(s)
- Supports NTSC or PAL
- Optional built-in audio receiver(s)

SI-300CC Camera Controller

Mechanical Specifications

Overall Dimensions: 3.5" H x 17.7" W x
10.5" D (8.8 cm x
44.8 cm x 26.6 cm)

Electrical Specifications

Power Requirements: 100-240 VAC, 50-60
Hz, 45 W

Communication Type: Fiber optic cable
(ST connectors); Bi-
direction asynchronous
serial 9600 baud

Display Resolution: 240 x 64 back-light
LCD

Channel Capacity: 4 fiber channels

Environmental Specifications

Ambient Temperature Limits

Operating: 0° to +40° C

Storage: -10° to +50° C

Humidity: Up to 90% non-
condensing

Ordering Information

Product: Camera Controller

Model Number: SI-300CC

Warranty: 1 year

To place an order or to learn more about the TDK RF Solutions products that best meet your needs, contact your TDK sales representative:

TDK RF Solutions Inc.

1101 Cypress Creek Rd.
Cedar Park, Texas 78613 USA

Phone: 1-512-258-9478

Fax: 1-512-258-0740

E-mail: info@tdkrf.com

World Wide Web: www.tdkrfsolutions.com

TDK Electronics Europe

TDK House, Queensway 5-7
RH1 1YB, Redhill, Surrey
United Kingdom

Phone: +44/1737-781-372

Fax: +44/1737-781-360

TOTAL RF EXPERTISE™



www.tdkrfsolutions.com

To learn more about TDK RF Solutions' wide range of innovative products and services visit www.tdkrfsolutions.com

© Copyright 2004 TDK RF Solutions Inc. All rights reserved. Specifications subject to change without notice.

DSSI300CC072604