



Electrical Properties:

Frequency Range: 902~928 MHz
 Impedance: 50Ω nominal
 VSWR: <2.0:1
 Gain: *2.0 dBi
 Radiation: Omni
 Polarization: Vertical
 Wave: Half Wave Dipole

Mechanical Properties:

Material:
 Whip: Polyurethane(Black)
 Connector: Brass with
 black chrome plating
 Operation Temp.: -20°C to +65°C
 Storage Temp.: -30°C to +75°C

TITLE	900 MHz ISM Band Swivel Antenna - 467 model		DATE	SHEET
			011305	1 of 2
UNIT	DWG. NO.	S467XX - 915S		
in.(mm)				
SCALE				
none				



SMA Plug
(AM)



TNC Plug
(TC)



BNC Plug
(BC)



SMA Plug Reverse Polarity
(AH)



TNC Plug Reverse Polarity
(TR)



BNC Plug Reverse Polarity
(BR)

Connector Type

Connector Code -XX-	Description	P / N
AM	SMA Plug	S467AM-915S
AH	SMA Plug Reverse Polarity	S467AH-915S
TC	TNC Plug	S467TC-915S
TR	TNC Plug Reverse Polarity	S467TR-915S
BC	BNC Plug	S467BC-915S
BR	BNC Plug Reverse Polarity	S467BR-915S

TITLE	900 MHz ISM Band Swivel Antenna - 467 model		DATE	SHEET
			011305	2 of 2
UNIT	DWG. NO.	S467XX - 915S		
in.(mm)				
SCALE				
none				