



	<b>PLB150</b>	<b>Units</b>
Load Voltage	250	V
Load Current	250	mA
Max R <sub>ON</sub>	7	Ω

### Description

PLB150 is a 250V, 250mA, 7Ω 1-Form-B relay. This performance leader provides high peak load current handling capability and very low on-resistance in a normally closed OptoMOS relay.

### Features

- Small 6 Pin DIP Package
- Low Drive Power Requirements (TTL/CMOS Compatible)
- No Moving Parts
- High Reliability
- Arc-Free With No Snubbing Circuits
- 3750V<sub>RMS</sub> Input/Output Isolation
- FCC Compatible
- VDE Compatible
- No EMI/RFI Generation
- Machine Insertable, Wave Solderable
- Surface Mount and Tape & Reel Versions Available

### Applications

- Telecommunications
  - Telecom Switching
  - Tip/Ring Circuits
  - Modem Switching (Laptop, Notebook, Pocket Size)
  - Hookswitch
  - Dial Pulsing
  - Ground Start
  - Ringer Injection
- Instrumentation
  - Multiplexers
  - Data Acquisition
  - Electronic Switching
  - I/O Subsystems
  - Meters (Watt-Hour, Water, Gas)
- Medical Equipment-Patient/Equipment Isolation
- Security
- Aerospace
- Industrial Controls

### Approvals

- UL Recognized: File Number E76270
- CSA Certified: File Number LR 43639-10
- BSI Certified:
  - BS EN 60950:1992 (BS7002:1992)  
Certificate #:7344
  - BS EN 41003:1993  
Certificate #:7344


### Ordering Information

<b>Part #</b>	<b>Description</b>
PLB150	6 Pin DIP (50/Tube)
PLB150S	6 Pin Surface Mount (50/Tube)
PLB150STR	6 Pin Surface Mount (1000/Reel)

### Pin Configuration


#### PLB150 Pinout

AC/DC Configuration




#### PLB150 Pinout

DC Only Configuration



### Switching Characteristics of Normally Closed (Form B) Devices



**Absolute Maximum Ratings (@ 25° C)**

Parameter	Min	Typ	Max	Units
Input Power Dissipation	-	-	150 <sup>1</sup>	mW
Input Control Current Peak (10ms)	-	-	50 1	mA A
Reverse Input Voltage	-	-	5	V
Total Power Dissipation	-	-	800 <sup>2</sup>	mW
Capacitance				
Input to Output	-	3	-	pF
Isolation Voltage Input to Output	3750	-	-	V <sub>RMS</sub>
Operational Temperature	-40	-	+85	°C
Storage Temperature	-40	-	+125	°C
Soldering Temperature DIP Package	-	-	-	-
Flatpack/Surface Mount Pkg (10 Seconds Max.)	-	-	+260 +220	°C

<sup>1</sup> Derate Linearly 1.33 mW/°C<sup>2</sup> Derate Linearly 6.67 mW/°C

*Absolute Maximum Ratings are stress ratings. Functional operation of the device at these or any other conditions beyond those indicated in the operational sections of this data sheet is not implied. Exposure of the device to the absolute maximum ratings for an extended period may degrade the device and effect its reliability.*

**Electrical Characteristics**

PARAMETER	CONDITIONS	SYMBOL	MIN	TYP	MAX	UNITS
<b>Output Characteristics @ 25°C</b>						
Load Voltage (Peak)	-	V <sub>L</sub>	-	-	250	V
Load Current* (Continuous)		I <sub>L</sub>	-	-	250	mA
AC/DC Configuration	-	I <sub>L</sub>	-	-	350	mA
DC Configuration		I <sub>LPK</sub>	-	-	500	mA
Peak Load Current	10ms	I <sub>LPK</sub>	-	-	7	Ω
On-Resistance		R <sub>ON</sub>	-	-	3	Ω
AC/DC Configuration	I <sub>L</sub> =250mA	R <sub>ON</sub>	-	-	1	μA
DC Configuration	I <sub>L</sub> =350mA	R <sub>ON</sub>	-	-	1.0	ms
Off-State Leakage Current	V <sub>L</sub> =250V	I <sub>LEAK</sub>	-	-	2.5	ms
Switching Speeds						
Turn-On	I <sub>F</sub> =5mA, V <sub>L</sub> =10V	T <sub>ON</sub>	-	-	110	pF
Turn-Off	I <sub>F</sub> =5mA, V <sub>L</sub> =10V	T <sub>OFF</sub>	-	-	-	-
Output Capacitance	50V; f=1MHz	C <sub>OUT</sub>	-	-	-	-
<b>Input Characteristics @ 25°C</b>						
Input Control Current	I <sub>L</sub> = 250mA	I <sub>F</sub>	5	-	50	mA
Input Dropout Current	-	I <sub>F</sub>	0.4	0.7	-	mA
Input Voltage Drop	I <sub>F</sub> = 5mA	V <sub>F</sub>	0.9	1.2	1.4	V
Reverse Input Voltage	-	V <sub>R</sub>	-	-	5	V
Reverse Input Current	V <sub>R</sub> =5V	I <sub>R</sub>	-	-	10	μA
Input to Output Capacitance	-	C <sub>I/O</sub>	-	3	-	pF
Input to Output Isolation	-	V <sub>I/O</sub>	3750	-	-	V <sub>RMS</sub>






\*NOTE: If both poles operate simultaneously load current must be derated so as not to exceed the package power dissipation value.



CLARE

PLB150

### Mechanical Dimensions

**6 Pin DIP Through Hole (Standard)****PC Board Pattern  
(Top View)****6 Pin DIP Surface Mount ("S" Suffix)****PC Board Pattern  
(Top View)****Tape and Reel Packaging for 6 Pin Surface Mount Package**

Dimensions  
mm  
(inches)



CLARE

---

**For additional information please visit our website at: [www.clare.com](http://www.clare.com)**

---

*Clare, Inc. makes no representations or warranties with respect to the accuracy or completeness of the contents of this publication and reserves the right to make changes to specifications and product descriptions at any time without notice. Neither circuit patent licenses nor indemnity are expressed or implied. Except as set forth in Clare's Standard Terms and Conditions of Sale, Clare, Inc. assumes no liability whatsoever, and disclaims any express or implied warranty, relating to its products including, but not limited to, the implied warranty of merchantability, fitness for a particular purpose, or infringement of any intellectual property right.*

---

*The products described in this document are not designed, intended, authorized or warranted for use as components in systems intended for surgical implant into the body, or in other applications intended to support or sustain life, or where malfunction of Clare's product may result in direct physical harm, injury, or death to a person or severe property or environmental damage. Clare, Inc. reserves the right to discontinue or make changes to its products at any time without notice.*

---

Specification: DS-PLB150-R3.0  
©Copyright 2002, Clare, Inc.  
All rights reserved. Printed in USA.  
6/25/02