

TOSHIBA Photocoupler Photorelay


TLP592A

Telecommunications
 Measurement and Control Equipment
 Data Acquisition System
 Measurement Equipment

Unit: mm


The Toshiba TLP592A consists of a gallium arsenide infrared emitting diode optically coupled to a photo-MOSFET in a 6-pin DIP package. This photorelay has higher output current rating than phototransistor-type photocoupler; hence, it is suitable for use as On/Off control for high current.

- Normally open (1-form-A) device
- Peak off-state voltage: 60 V (min)
- Trigger LED current: 3 mA (max)
- On-state current: 500 mA (max)
- On-state resistance: 2 Ω (max)
- Isolation voltage: 2500 Vrms (min)
- UL recognized: UL1557, File No.E67349




Weight: 0.4 g (typ.)

Pin Configuration (top view)



Schematic



最大定格 (Ta = 25°C)


| Characteristics | | Symbol | Rating | Unit | |
|---|---|-----------------------------|--------------------------------|-------|-------|
| LED | Forward current | I_F | 50 | mA | |
| | Forward current derating ($T_a \geq 25^\circ\text{C}$) | $\Delta I_F/^\circ\text{C}$ | -0.5 | mA/°C | |
| | Peak forward current (100 μs pulse, 100 pps) | I_{FP} | 1 | A | |
| | Reverse voltage | V_R | 5 | V | |
| | Junction temperature | T_j | 125 | °C | |
| Detector | Off-state output terminal voltage | V_{OFF} | 60 | V | |
| | On-state current | A connection | I_{ON} | 500 | mA |
| | | B connection | | 500 | |
| | | C connection | | 1000 | |
| | Forward current derating ($T_a \geq 25^\circ\text{C}$) | A connection | $\Delta I_{ON}/^\circ\text{C}$ | -5.0 | mA/°C |
| | | B connection | | -5.0 | |
| | | C connection | | -10.0 | |
| Junction temperature | T_j | 125 | °C | | |
| Storage temperature | | T_{stg} | -55 to 125 | °C | |
| Operating temperature | | T_{opr} | -40 to 85 | °C | |
| Lead soldering temperature (10 s) | | T_{sol} | 260 | °C | |
| Isolation voltage (AC, 1 min, R.H. $\leq 60\%$) (Note 1) | | BV_S | 2500 | Vrms | |

Note 1: LED pins are shorted together. Detector pins are also shorted together.

Recommended Operating Conditions

| Characteristics | Symbol | Min | Typ. | Max | Unit |
|-----------------------|-----------|-----|------|-----|------|
| Supply voltage | V_{DD} | — | — | 48 | V |
| Forward current | I_F | 5 | 7.5 | 25 | mA |
| On-state current | I_{ON} | — | — | 500 | mA |
| Operating temperature | T_{opr} | -20 | — | 65 | °C |

Circuit Connections



Electrical Characteristics (Ta = 25°C)

| Characteristics | | Symbol | Test Condition | Min | Typ. | Max | Unit |
|-----------------|-------------------|-----------|----------------------------|-----|------|-----|---------------|
| LED | Forward voltage | V_F | $I_F = 10 \text{ mA}$ | 1.0 | 1.15 | 1.3 | V |
| | Reverse voltage | I_R | $V_R = 5 \text{ V}$ | — | — | 10 | μA |
| | Capacitance | C_T | $V = 0, f = 1 \text{ MHz}$ | — | 30 | — | pF |
| Detector | Off-state current | I_{OFF} | $V_{OFF} = 60 \text{ V}$ | — | — | 1 | μA |
| | Capacitance | C_{OFF} | $V = 0, f = 1 \text{ MHz}$ | — | 130 | — | pF |

Coupled Electrical Characteristics (Ta = 25°C)

| Characteristics | | Symbol | Test Condition | Min | Typ. | Max | Unit |
|---------------------|--------------|----------|--|-----|------|-----|----------|
| Trigger LED current | | I_{FT} | $I_{ON} = 500 \text{ mA}$ | — | 1.6 | 3 | mA |
| Return LED current | | I_{FC} | $I_{OFF} = 100 \mu\text{A}$ | 0.1 | — | — | mA |
| On-state resistance | A connection | R_{ON} | $I_{ON} = 500 \text{ mA}, I_F = 5 \text{ mA}$ | — | 1 | 2 | Ω |
| | B connection | | $I_{ON} = 500 \text{ mA}, I_F = 5 \text{ mA}$ | — | 0.5 | 1 | |
| | C connection | | $I_{ON} = 1000 \text{ mA}, I_F = 5 \text{ mA}$ | — | 0.25 | — | |


Isolation Characteristics (Ta = 25°C)







| Characteristics | | Symbol | Test Condition | Min | Typ. | Max | Unit |
|-----------------------------|--|--------|--|--------------------|-----------|-----|----------|
| Capacitance input to output | | C_S | $V_S = 0 \text{ V}, f = 1 \text{ MHz}$ | — | 0.8 | — | pF |
| Isolation resistance | | R_S | $V_S = 500 \text{ V}, \text{R.H.} \leq 60\%$ | 5×10^{10} | 10^{14} | — | Ω |
| Isolation voltage | | BV_S | AC, 1 min | 2500 | — | — | Vrms |
| | | | AC, 1 s, in oil | — | 5000 | — | |
| | | | DC, 1 min, in oil | — | 5000 | — | Vdc |




Switching Characteristics (Ta = 25°C)

| Characteristics | | Symbol | Test Condition | Min | Typ. | Max | Unit |
|-----------------|-----------|-----------------------------|---|-----|------|-----|------|
| Turn-on time | t_{ON} | $R_L = 200 \Omega$ (Note 2) | $V_{DD} = 20 \text{ V}, I_F = 5 \text{ mA}$ | — | 0.8 | 2 | ms |
| Turn-off time | t_{OFF} | | | — | 0.1 | 0.5 | |

Note 2: Switching time test circuit







RESTRICTIONS ON PRODUCT USE

000707EAC

- TOSHIBA is continually working to improve the quality and reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to comply with the standards of safety in making a safe design for the entire system, and to avoid situations in which a malfunction or failure of such TOSHIBA products could cause loss of human life, bodily injury or damage to property.
In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent TOSHIBA products specifications. Also, please keep in mind the precautions and conditions set forth in the "Handling Guide for Semiconductor Devices," or "TOSHIBA Semiconductor Reliability Handbook" etc..
- The TOSHIBA products listed in this document are intended for usage in general electronics applications (computer, personal equipment, office equipment, measuring equipment, industrial robotics, domestic appliances, etc.). These TOSHIBA products are neither intended nor warranted for usage in equipment that requires extraordinarily high quality and/or reliability or a malfunction or failure of which may cause loss of human life or bodily injury ("Unintended Usage"). Unintended Usage include atomic energy control instruments, airplane or spaceship instruments, transportation instruments, traffic signal instruments, combustion control instruments, medical instruments, all types of safety devices, etc.. Unintended Usage of TOSHIBA products listed in this document shall be made at the customer's own risk.
- Gallium arsenide (GaAs) is a substance used in the products described in this document. GaAs dust and fumes are toxic. Do not break, cut or pulverize the product, or use chemicals to dissolve them. When disposing of the products, follow the appropriate regulations. Do not dispose of the products with other industrial waste or with domestic garbage.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.
- The information contained herein is subject to change without notice.