


PACKAGE DIMENSIONS



DESCRIPTION

The F5F1 is a 940nm LED encapsulated in a clear, wide angle, sidelooper package.

FEATURES

- Good optical to mechanical alignment
- Mechanically and wavelength matched to the L14Q series phototransistor
- Plastic package with a color stripe for easy recognition from phototransistor
- High irradiance level

ST1334

SYMBOL	MILLIMETERS		INCHES		NOTES
	MIN.	MAX.	MIN.	MAX.	
A	5.59	5.80	.220	.228	
B	1.78	NOM.	.070	NOM.	2
φb	.60	.75	.024	.030	1
b ₁	.51	NOM.	.020	NOM.	1
D	4.45	4.70	.175	.185	
E	2.41	2.67	.095	.105	
E ₁	.58	.69	.023	.027	
e	2.41	2.67	.095	.105	3
G	1.98	NOM.	.078	NOM.	
L	12.7	—	.500	—	
L ₁	1.40	1.65	.055	.065	
S	.83	.94	.033	.037	3

PACKAGE OUTLINE



NOTES:

1. TWO LEADS. LEAD CROSS SECTION DIMENSIONS UNCONTROLLED WITHIN 1.27 mm (.050") OF SEATING PLANE.
2. CENTERLINE OF ACTIVE ELEMENT LOCATED WITHIN .25 mm (.010") OF TRUE POSITION.
3. AS MEASURED AT THE SEATING PLANE.
4. INCH DIMENSIONS DERIVED FROM MILLIMETERS.

ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$ Unless Otherwise Specified)	
Storage Temperature	-55°C to $+100^\circ\text{C}$
Operating Temperature	-55°C to $+100^\circ\text{C}$
Soldering:	
Lead Temperature (Iron)	240°C for 5 sec. ^(2,3,4,5)
Lead Temperature (Flow)	260°C for 10 sec. ^(2,3,5)
Continuous Forward Current	60 mA
Forward Current (pw, $1\mu\text{S}$; $\leq 33\text{ Hz}$)	3 A
Reverse Voltage	6 Volts
Power Dissipation	100 mW ⁽¹⁾

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ Unless Otherwise Specified) (All measurements made under pulse conditions.)						
PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNITS	TEST CONDITIONS
Forward Voltage	V_f	—		1.7	V	$I_f = 60\text{ mA}$
Reverse Breakdown Voltage	V_R	6		—	V	$I_R = 10\ \mu\text{A}$
Reverse Leakage Current	I_R	—		10	μA	$V_R = 5\text{ V}$
Peak Emission Wavelength	λ_p		940		nm	$I_f = 100\text{ mA}$
Emission Angle at 1/2 Power	θ		± 35		Degrees	
Radiant Intensity	I_e	0.28		—	mW/sr	$I_f = 20\text{ mA}^{(6)}$

NOTES
<ol style="list-style-type: none"> 1. Derate power dissipation linearly 1.33 mW/$^\circ\text{C}$ above 25°C ambient. 2. RMA flux is recommended. 3. Methanol or Isopropanol alcohols are recommended as cleaning agents. 4. Soldering iron tip $\frac{1}{16}$" (1.6 mm) minimum from housing. 5. As long as leads are not under any stress or spring tension. 6. I_e measured with a 0.45 cm aperture placed 1.6 cm from the tip of the lens on the lens centerline perpendicular to the plane of the leads.

TYPICAL CHARACTERISTICS




Fig. 1. Radiant Intensity vs. Input Current

ST1033




Fig. 2. Radiant Intensity vs. Temperature

ST1038




Fig. 3. Forward Voltage vs. Temperature

ST1034




Fig. 4. Leakage Current vs. Temperature

ST1037




Fig. 5. Spectral Response

ST1035




Fig. 6. Typical Radiation Pattern

ST1036



GaAs INFRARED EMITTING DIODE

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.