


Silicon PIN Photodiode, RoHS Compliant



FEATURES

- Package type: surface mount
- Package form: GW, RGW, yoke, axial
- Dimensions (L x W x H in mm): 2.5 x 2 x 2.7
- Radiant sensitive area (in mm²): 0.23
- High radiant sensitivity
- Daylight blocking filter matched with 870 nm to 950 nm emitters
- Fast response times
- Angle of half sensitivity: $\phi = \pm 15^\circ$
- Package matches with IR emitter series TSMF1000
- Floor life: 168 h, MSL 3, acc. J-STD-020
- Lead (Pb)-free component in accordance with RoHS 2002/95/EC and WEEE 2002/96/EC



RoHS
COMPLIANT

DESCRIPTION

TEMD1000 series are PIN photodiodes with high speed and high radiant sensitivity in black, surface mount plastic packages with lens and daylight blocking filter. Filter bandwidth is matched with 870 nm to 950 nm IR emitters.

APPLICATIONS

- High speed detector for infrared radiation
- Infrared remote control and free air data transmissionsystems, e.g. in combination with TSFFxxxx series IR emitters

| PRODUCT SUMMARY | | | |
|-----------------|---------------|--------------|----------------------|
| COMPONENT | I_{ra} (mA) | ϕ (deg) | $\lambda_{0.5}$ (nm) |
| TEMD1000 | 12 | ± 15 | 790 to 1050 |
| TEMD1020 | 12 | ± 15 | 790 to 1050 |
| TEMD1030 | 12 | ± 15 | 790 to 1050 |
| TEMD1040 | 12 | ± 15 | 790 to 1050 |

Note

Test conditions see table "Basic Characteristics"

| ORDERING INFORMATION | | | |
|----------------------|---------------|------------------------------|------------------|
| ORDERING CODE | PACKAGING | REMARKS | PACKAGE FORM |
| TEMD1000 | Tape and reel | MOQ: 1000 pcs, 1000 pcs/reel | Reverse gullwing |
| TEMD1020 | Tape and reel | MOQ: 1000 pcs, 1000 pcs/reel | Gullwing |
| TEMD1030 | Tape and reel | MOQ: 1000 pcs, 1000 pcs/reel | Yoke |
| TEMD1040 | Bulk | MOQ: 1000 pcs, 1000 pcs/bulk | Axial leads |

Note

MOQ: minimum order quantity

| ABSOLUTE MAXIMUM RATINGS | | | | |
|-----------------------------|---------------------------------|-----------|---------------|------------------|
| PARAMETER | TEST CONDITION | SYMBOL | VALUE | UNIT |
| Reverse voltage | | V_R | 60 | V |
| Power dissipation | $T_{amb} \leq 25^\circ\text{C}$ | P_V | 75 | mW |
| Junction temperature | | T_j | 100 | $^\circ\text{C}$ |
| Operating temperature range | | T_{amb} | - 40 to + 85 | $^\circ\text{C}$ |
| Storage temperature range | | T_{stg} | - 40 to + 100 | $^\circ\text{C}$ |
| Soldering temperature | $t \leq 5$ s | T_{sd} | < 260 | $^\circ\text{C}$ |

Note

$T_{amb} = 25^\circ\text{C}$, unless otherwise specified



| BASIC CHARACTERISTICS | | | | | | |
|-------------------------------------|--|-----------------|------|-------------|------|---------------|
| PARAMETER | TEST CONDITION | SYMBOL | MIN. | TYP. | MAX. | UNIT |
| Forward voltage | $I_F = 50 \text{ mA}$ | V_F | | 1 | 1.3 | V |
| Breakdown voltage | $I_R = 100 \text{ } \mu\text{A}, E = 0$ | $V_{(BR)}$ | 60 | | | V |
| Reverse dark current | $V_R = 10 \text{ V}, E = 0$ | I_{ro} | | 1 | 10 | nA |
| Diode capacitance | $V_R = 5 \text{ V}, f = 1 \text{ MHz}, E = 0$ | C_D | | 1.8 | | pF |
| Reverse light current | $E_e = 1 \text{ mW/cm}^2, \lambda = 870 \text{ nm}, V_R = 5 \text{ V}$ | I_{ra} | | 10 | | μA |
| | $E_e = 1 \text{ mW/cm}^2, \lambda = 950 \text{ nm}, V_R = 5 \text{ V}$ | I_{ra} | 5 | 12 | | μA |
| Temperature coefficient of I_{ra} | $V_R = 5 \text{ V}, \lambda = 870 \text{ nm}$ | $TK_{I_{ra}}$ | | 0.2 | | %/K |
| Absolute spectral sensitivity | $V_R = 5 \text{ V}, \lambda = 870 \text{ nm}$ | $s(\lambda)$ | | 0.60 | | A/W |
| | $V_R = 5 \text{ V}, \lambda = 950 \text{ nm}$ | $s(\lambda)$ | | 0.55 | | A/W |
| Angle of half sensitivity | | φ | | ± 15 | | deg |
| Wavelength of peak sensitivity | | λ_p | | 940 | | nm |
| Range of spectral bandwidth | | $\lambda_{0.5}$ | | 790 to 1050 | | nm |
| Rise time | $V_R = 10 \text{ V}, R_L = 50 \text{ } \Omega, \lambda = 820 \text{ nm}$ | t_r | | 4 | | ns |
| Fall time | $V_R = 10 \text{ V}, R_L = 50 \text{ } \Omega, \lambda = 820 \text{ nm}$ | t_f | | 4 | | ns |

Note

$T_{amb} = 25 \text{ }^\circ\text{C}$, unless otherwise specified

BASIC CHARACTERISTICS

$T_{amb} = 25 \text{ }^\circ\text{C}$, unless otherwise specified




Fig. 1 - Reverse Dark Current vs. Ambient Temperature




Fig. 2 - Relative Reverse Light Current vs. Ambient Temperature




Fig. 3 - Reverse Light Current vs. Irradiance




Fig. 5 - Relative Spectral Sensitivity vs. Wavelength




Fig. 4 - Diode Capacitance vs. Reverse Voltage




Fig. 6 - Relative Radiant Sensitivity vs. Angular Displacement

PRECAUTIONS FOR USE

1. Over-current-proof

Customer must apply resistors for protection, otherwise slight voltage shift will cause big current change (burn out will happen).

2. Storage

2.1 Storage temperature and rel. humidity conditions are: 5 °C to 35 °C, R.H. 60 %.

2.2 Floor life must not exceed 168 h, acc. to JEDEC level 3, J-STD-020.

Once the package is opened, the products should be used within a week. Otherwise, they should be kept in a damp proof box with desiccant. Considering tape life, we suggest to use products within one year from production date.

2.3 If opened more than one week in an atmosphere 5 °C to 35 °C, R.H. 60 %, devices should be treated at 60 °C ± 5 °C for 15 h.

2.4 If humidity indicator in the package shows pink color (normal blue), then devices should be treated with the same conditions as 2.3.

REFLOW SOLDER PROFILE





Fig. 7 - Lead Tin (SnPb) Reflow Solder Profile



TEMD1000, TEMD1020, TEMD1030, TEMD1040


Silicon PIN Photodiode, RoHS Compliant Vishay Semiconductors

PACKAGE DIMENSIONS in millimeters: TEMD1000



Drawing-No.: 6.544-5326.02-4
Issue: 3; 02.04.03
16159

PACKAGE DIMENSIONS in millimeters: TEMD1020



Drawing-No.: 6.544-5325.02-4
Issue: 3; 02.04.03


16160

TEMD1000, TEMD1020, TEMD1030, TEMD1040

Vishay Semiconductors Silicon PIN Photodiode, RoHS Compliant





PACKAGE DIMENSIONS in millimeters: TEMD1030




Drawing-No.: 6.544-5329.01-4

Issue: 4; 08.05.03





Solder pad proposal



16228

PACKAGE DIMENSIONS in millimeters: TEMD1040



Drawing-No.: 6.544-5339.02-4

Issue: 3; 02.04.03


16760




TEMD1000, TEMD1020, TEMD1030, TEMD1040

Silicon PIN Photodiode, RoHS Compliant Vishay Semiconductors


REEL DIMENSIONS in millimeters



Leader and trailer tape:



TAPING DIMENSIONS in millimeters: TEMD1000



Quantity per reel: 1000 pcs or 5000 pcs


18030

TEMD1000, TEMD1020, TEMD1030, TEMD1040


Vishay Semiconductors Silicon PIN Photodiode, RoHS Compliant



TAPING DIMENSIONS in millimeters: TEMD1020



TAPING DIMENSIONS in millimeters: TEMD1030





Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.