

SonaSwitch®

Series 1650A & 1650S

ULTRASONIC SENSORS

Technical Specifications



RANGE

6" to 10' adjustable; $\pm 0.1\%$ accuracy over entire range at stable temperatures; Switchpoint and analog outputs are temperature compensated.

BEAM ANGLE

15 degree nominal; Single beam, cone-shaped pattern diverges approximately 2.6' at maximum range (10').

REPETITION RATE

10HZ astable; May be externally triggered

RELAY RESPONSE TIME

0.50 seconds nominal from start of detection to relay closure; 0.50 second nominal shut-off time.

OUTPUTS

Model 1650S

Two (2) adjustable Form C relay outputs (NO/NC); Relay continuously energized during detection period (Relay contacts rated at 0.4 amps, 125 VAC resistive or 1.25 amps, 24 VAC resistive).

Model 1650A

One (1) 0-5 VDC or 0-10 VDC 8-bit analog output with fully independent zero and span adjustments over entire operating range.

OPERATING TEMPERATURE

Approximately -40 to 85°C (-40 to 185°F).

ENVIRONMENT

Indoor or protected environments; Highly insensitive to temperature, humidity and pressure changes; Withstands high audio and EMI/RFI levels; Must be protected from excessive moisture in outdoor applications.

SIZE

5.72cm W x 8.89cm H x 2.29cm D
(2.25" W x 3.50" H x 0.90"D).

WEIGHT

Approximately 7.0 ounces.

CASE MATERIAL

High temperature electroplated ABS Plastic.

POWER REQUIREMENTS


12-30 VDC or 12-24 VAC; 0.15 amps maximum current; 0.08 amps average current.

MOUNTING REQUIREMENTS

Two (2) No. 10 (5/32) machine screws mounted flat on 1.85" centers; Supplied with 6' cable.

COLOR

Medium blue; Optional colors available.



Visit us on the Internet:
www.edpcompany.com

Red	12-30 VDC or
Black	12-24 VAC
White	NO Relay 1
Yellow	Common Relay 1
Orange	NC Relay 1
Blue	Trigger In
Brown	Trigger Source Out
Tan	Ext. Trigger Enable
Violet	NO Relay 2
Gray	Common Relay 2
Pink	NC Relay 2
Green	Common

36704 Commerce Rd. • Livonia, MI 48150
Outside U.S.A. Phone 734-591-9176 • FAX 734-591-7852

TOLL FREE 1-800-553-9070