



**MISCELLANEOUS SOCKETS**  
**Shrink DIP Sockets and Strips**  
**Solder Tail and Wrapost**

**Series 117, 127, 217**  
**227, 317, 327**

- High density DIP sockets and strips for devices featuring .070" lead spacing.
- Solder tails use MM #1802 receptacles, See page 138 for details. Wraposts use MM #1702-2 or 1703-3 receptacles, See page 162 for details.
- Receptacles use Hi-Rel, 4-finger #30 contact and 6-finger #43 contact, both rated at 3 amps. See pages 208 & 209.
- Insulators are high temp. thermoplastic.

Total number of pins				Quantity per tube	<b>Ordering Information</b>			
	A	B	C					
					Solder Tail	2 Level Wrapost L = .370	3 Level Wrapost L = .510	
<b>OPEN FRAME DIP SOCKET</b>								
16	0.572	0.3	0.39	35	117-XX-316-41-005000	127-XX-316-41-002000	127-XX-316-41-003000	
28	0.992	0.4	0.49	20	117-XX-428-41-005000	127-XX-428-41-002000	127-XX-428-41-003000	
30	1.062	0.4	0.49	18	117-XX-430-41-005000	127-XX-430-41-002000	127-XX-430-41-003000	
48	1.692	0.4	0.49	12	117-XX-448-41-005000	127-XX-448-41-002000	127-XX-448-41-003000	
20	0.712	0.6	0.69	28	117-XX-620-41-005000	127-XX-620-41-002000	127-XX-620-41-003000	
28	0.992	0.6	0.69	20	117-XX-628-41-005000	127-XX-628-41-002000	127-XX-628-41-003000	
40	1.412	0.6	0.69	14	117-XX-640-41-005000	127-XX-640-41-002000	127-XX-640-41-003000	
42	1.482	0.6	0.69	13	117-XX-642-41-005000	127-XX-642-41-002000	127-XX-642-41-003000	
48	1.692	0.6	0.69	11	117-XX-648-41-005000	127-XX-648-41-002000	127-XX-648-41-003000	
52	1.832	0.6	0.69	11	117-XX-652-41-005000	127-XX-652-41-002000	127-XX-652-41-003000	
56	1.972	0.6	0.69	10	117-XX-656-41-005000	127-XX-656-41-002000	127-XX-656-41-003000	
64	2.252	0.6	0.69	8	117-XX-664-41-005000	127-XX-664-41-002000	127-XX-664-41-003000	
68	2.392	0.6	0.69	8	117-XX-668-41-005000	127-XX-668-41-002000	127-XX-668-41-003000	
64	2.252	0.75	0.84	8	117-XX-764-41-005000	127-XX-764-41-002000	127-XX-764-41-003000	
<b>CLOSED FRAME DIP SOCKET</b>								
64	2.252	0.75	0.84	8	217-XX-764-41-005000	227-XX-764-41-002000	227-XX-764-41-003000	
<b>SINGLE ROW STRIP SOCKET</b>								
If desired, we will supply any length up to 21 pins.								
21	1.482				317-XX-121-41-005000	327-XX-121-41-002000	327-XX-121-41-003000	
					SPECIFY PLATING CODE XX=	13	93	43
					Sleeve (Pin)	10µ" Au	200µ" Sn/Pb	200µ" Sn
					Contact (Clip)	30µ" Au	30µ" Au	30µ" Au