

<h3>0501</h3> <p>0501-0-15-XX-30-XX-04-0 Press-fit in .057 mounting hole</p>	<h3>8427</h3> <p>8427-0-15-XX-30-XX-04-0 Press-fit in .057 mounting hole</p>	<h3>1434</h3> <p>1434-0-15-XX-30-XX-10-0 Press-fit in .055 mounting hole</p>	<h3>9970</h3> <p>9970-0-15-XX-30-XX-04-0 Square press-fit for .032 ±.002 plated thru hole</p>
---	---	---	--

<h3>5970</h3> <p>5970-X-15-XX-32-XX-04-0 Square press-fit for .032 or .039 ±.002 plated thru hole</p>	<table border="1"> <thead> <tr> <th>Basic Part Number</th> <th>U Square</th> <th>Mounting Hole</th> </tr> </thead> <tbody> <tr> <td>5970-1</td> <td>.028</td> <td>.032</td> </tr> <tr> <td>5970-2</td> <td>.034</td> <td>.039</td> </tr> </tbody> </table>	Basic Part Number	U Square	Mounting Hole	5970-1	.028	.032	5970-2	.034	.039	<h3>0477/0478</h3> <p>047X-0-18-XX-30-XX-04-0 Solderless press-fit in .038 +.003 / -.002 plated thru hole (use 1.1mm drill prior to plating)</p>	<table border="1"> <thead> <tr> <th>Basic Part Number</th> <th>Board Thickness</th> <th>Length V</th> <th>Length A</th> </tr> </thead> <tbody> <tr> <td>0477-0</td> <td>.062</td> <td>.075</td> <td>.175</td> </tr> <tr> <td>0478-0</td> <td>.125</td> <td>.140</td> <td>.250</td> </tr> </tbody> </table>	Basic Part Number	Board Thickness	Length V	Length A	0477-0	.062	.075	.175	0478-0	.125	.140	.250
Basic Part Number	U Square	Mounting Hole																						
5970-1	.028	.032																						
5970-2	.034	.039																						
Basic Part Number	Board Thickness	Length V	Length A																					
0477-0	.062	.075	.175																					
0478-0	.125	.140	.250																					

<h3>4612</h3> <p>4612-0-31-XX-30-XX-04-0 Compliant press-fit in .040 ±.003 plated hole. For .060 → .100 thick board</p>	<h3>4613</h3> <p>4613-0-31-XX-30-XX-04-0 Compliant press-fit in .040 ±.003 plated hole. For .090 → .130 thick board</p>	<h3>0680</h3> <p>0680-0-15-XX-32-XX-10-0 Solder mount in .051 min. mounting hole</p>	<h3>0149</h3> <p>0149-0-15-XX-30-XX-04-0 Press-fit in .059 mounting hole</p>
--	--	---	---

<h3>SPECIFICATIONS</h3> <p>SHELL MATERIAL: Brass Alloy 360, 1/2 Hard</p> <p>CONTACT MATERIAL: Beryllium Copper Alloy 172, HT</p> <p>DIMENSION IN INCHES TOLERANCES ON: LENGTHS: ±.005 DIAMETERS: ±.002 ANGLES: ± 2°</p>	<p>ORDER CODE: XXXX - X - XX - XX - 3X - XX - XX - 0</p> <p>BASIC PART # →</p> <p>SPECIFY SHELL FINISH:</p> <ul style="list-style-type: none"> 01 200µ" TIN/LEAD OVER NICKEL 80 200µ" TIN OVER NICKEL 15 10µ" GOLD OVER NICKEL <p>SPECIFY CONTACT FINISH:</p> <ul style="list-style-type: none"> 02 100µ" TIN/LEAD OVER NICKEL 84 100µ" TIN OVER NICKEL 27 30µ" GOLD OVER NICKEL <p>SELECT CONTACT #30 or #32 CONTACT (DATA ON PAGE 208)</p>
--	---

