

9808	9101	5650	8679
<b>9808-0-15-XX-16-XX-04-0</b> Press-fit in .067 mounting hole	<b>9101-0-15-XX-16-XX-10-0</b> Press-fit in .067 mounting hole	<b>5650-0-19-XX-16-XX-10-0</b> Press-fit in .067 mounting hole	<b>8679-0-15-XX-16-XX-10-0</b> Solder mount in .071 min. mounting hole

8827	6021	1873
<b>8827-0-15-XX-16-XX-04-0</b> Press-fit in .061 mounting hole	<b>6021-0-15-XX-16-XX-10-0</b> Solder mount in .062 min. mounting hole	<b>1873-0-15-XX-16-XX-04-0</b> Press-fit in .066 mounting hole

--	--	--	--

<p><b>SPECIFICATIONS</b></p> <p><b>SHELL MATERIAL:</b> Brass Alloy 360, 1/2 Hard</p> <p><b>CONTACT MATERIAL:</b> Beryllium Copper Alloy 172, HT</p> <p><b>DIMENSION IN INCHES</b> <b>TOLERANCES ON:</b> LENGTHS: ±.005 DIAMETERS: ±.002 ANGLES: ± 2°</p>	<p><b>ORDER CODE: XXXX - X - 15 - XX - 16 - XX - XX - 0</b></p> <p><b>BASIC PART #</b> →</p> <p><b>SPECIFY SHELL FINISH:</b></p> <p><b>01</b> 200μ" TIN/LEAD OVER NICKEL</p> <p><b>80</b> 200μ" TIN OVER NICKEL ◇</p> <p><b>15</b> 10μ" GOLD OVER NICKEL ◇</p> <p style="text-align: center;"><b>CONTACT</b></p> <p style="text-align: center;">#16 CONTACT (DATA ON PAGE 210)</p> <p style="text-align: center;"></p>
--	--