

<b>0669</b>	<b>0670</b>	<b>0673</b>	<b>0666</b>
<b>0669-0-15-XX-30-XX-10-0</b> Solder mount in .060 min. mounting hole	<b>0670-0-15-XX-30-XX-10-0</b> Solder mount in .060 min. mounting hole	<b>0673-0-15-XX-30-XX-10-0</b> Surface Mount	<b>0666-0-15-XX-32-XX-10-0</b> Solder mount in .064 min. mounting hole

<b>0341</b>	<b>0252</b>	<b>0678</b>	<b>0676</b>
<b>0341-0-15-XX-30-XX-10-0</b> Press-fit in .073 mounting hole	<b>0252-0-15-XX-32-XX-10-0</b> Hex press-fit in .057 plated thru hole	<b>0678-0-15-XX-32-XX-10-0</b> Press-fit in .057 mounting hole	<b>0676-0-15-XX-30-XX-10-0</b> Press-fit in .057 mounting hole

<b>0697</b>	<b>0668</b>	<b>0253/1033</b>
<b>0697-0-15-XX-30-XX-10-0</b> Press-fit in .057 mounting hole	<b>0668-0-15-XX-30-XX-10-0</b> Press-fit in .057 mounting hole	<b>XXX3-0-15-XX-30-XX-10-0</b> Press-fit in .057 mounting hole

Basic Part Number	Length L	Depth N
0253-0	.173	.148
1033-0	.203	.162

<p><b>SPECIFICATIONS</b></p> <p><b>SHELL MATERIAL:</b> Brass Alloy 360, 1/2 Hard</p> <p><b>CONTACT MATERIAL:</b> Beryllium Copper Alloy 172, HT</p> <p><b>DIMENSION IN INCHES</b></p> <p><b>TOLERANCES ON:</b></p> <p>LENGTHS: ±.005</p> <p>DIAMETERS: ±.002</p> <p>ANGLES: ± 2°</p>	<p><b>ORDER CODE: <u>XXXX</u> - 0 - 15 - <u>XX</u> - <u>3X</u> - <u>XX</u> - 10 - 0</b></p> <p><b>BASIC PART #</b> →</p> <p><b>SPECIFY SHELL FINISH:</b> →</p> <p><b>01</b> 200μ" TIN/LEAD OVER NICKEL</p> <p><b>15</b> 10μ" GOLD OVER NICKEL</p> <p align="center"><b>SELECT CONTACT</b></p> <p align="center"><b>#30 OR #32 CONTACT (DATA ON PAGE 208)</b></p> <p><b>SPECIFY CONTACT FINISH:</b> →</p> <p><b>02</b> 200μ" TIN/LEAD OVER NICKEL</p> <p><b>14</b> 10μ" GOLD OVER NICKEL</p> <p><b>27</b> 30μ" GOLD OVER NICKEL</p>
--	--