



Description:

This product is designed for use in ESD controlled areas where there are ESDsensitive devices. This product is constructed out of 6 mil, clear, permanently dissipative polyethylene film. Drawing protectors are designed to provide static control packaging for holding engineering drawings or other large documents. This product meets or exceeds the requirements of MIL-B-81705C, Type II.

Amine-free.
N-Octanoic acid free.
Humidity independent.
Does not promote corrosion.
Has no measurable outgassing.

Electrical Properties:

Static Decay:	< 1.0 sec.	per FTMS 101C, Method 4046
Surface Resistivity:	10 ¹⁰ - 10 ¹² Ohms/sq.	per ASTM D-257

Specifications:

Polycarbonate haze:	Negligible	72 hr contact
Corrosivity:	Neglibible	per FTMS 101C, Method 3005
Melt Index:	.050 gm/10 min.	per ASTM D-1238
Density:	0.923 gm/cc	per ASTM D-1505
Haze:	10%	per ASTM D-1003
60° gloss:	90	per ASTM D-2457
45° gloss:	56	per ASTM D-2457
Dart impact:	230 gms	per ASTM D-1709
Coefficient of friction:	0.50	per ASTM D-1894
1% secant modulus:	MD 24,000 psi	per ASTM D-882
Stiffness:	MD 25,000 psi	per ASTM D-882

A. B size drawing holder will hold up to an 11" x 17" sheet size.

Wording across bottom area:

"DESCO STATIC SAFE B SIZE DRAWING PROTECTOR ITEM #07453"

DRAWING PROTECTOR, STATIC SAFE, 6 MIL

DESCO

DESCO WEST: 3651 WALNUT AVE., CHINO, CA 91710 WEB SITE: www.desco.com
PHONE (909) 627-8178 FAX (909) 627-7449 FAX REQUEST (909) 627-7126
DESCO EAST: 90 HUDSON RD, CANTON, MA 02021-1407
PHONE (781) 821-8370 FAX (781) 575-0172

DRAWING NUMBER
07453

DATE:
8/01