



**Description:**

This product is designed for use in ESD controlled areas where there are electrostatic sensitive devices. All shop travelers are made from a stable, amine-free, clear, static dissipative polyethylene, 6 Mil thick film. Dissipative agent is extruded in and is slow blooming with an effective shelf life in excess of two years. These products are designed to hold an 8 1/2" x 11" sheet and can be cleaned for use in Class 100 Clean Rooms.

Humidity independent.  
N-Octanoic Acid Free.  
Does not promote corrosion.  
Has no measurable outgassing.

**Electrical Properties:**

Static Decay:	< 1.0 sec.	per FTMS 101C, Method 4046
Surface Resistivity:	10 <sup>10</sup> - 10 <sup>12</sup> Ohms/sq.	per ASTM D-257
Polycarbonate Haze:	Negligible	per 72 hour contact
Corrosivity:	Negligible	per FTMS 101C-3005

**Specifications:**

Melt Index:	.050 gm/10 min.	per ASTM D-1238
Density:	0.923 gm/cc	per ASTM D-1505
Haze:	10%	per ASTM D-1003
60° gloss:	90	per ASTM D-2457
45° gloss:	56	per ASTM D-2457
Dart impact:	230 gms	per ASTM D-1709
Coefficient of friction:	0.50	per ASTM D-1894

A. Both shop travelers are hot stamped with:

"STATIC SAFE  
SHOP TRAVELER  
DESCO INDUSTRIES  
ITEM # \_\_\_\_\_"

**SHOP TRAVELER, STATIC SAFE, 6 MIL**



DESCO WEST: 3651 WALNUT AVE., CHINO, CA 91710 WEB SITE: www.desco.com  
PHONE (909) 627-8178 FAX (909) 627-7449 FAX REQUEST (909) 627-7126

DESCO EAST: 90 HUDSON RD, CANTON, MA 02021-1407  
PHONE (781) 821-8370 FAX (781) 575-0172

**DRAWING NUMBER**  
07471

**DATE:**  
6/99