



DISSIPATIVE PINK POLY



Specifications:

Electrical Properties

Static Decay
 Surface Resistance
 Polycarbonate Haze
 Corrosivity Observations

Typical Values

<1.0 sec.
 < 10¹¹ Ohms
 NE
 NE

Test Procedures/Method

ASTM 101 Method 4046
 ESD S11.11
 72 hr contact
 MIL-STD-3010, M3005

Physical Properties

Thickness
 Melt Index
 Density
 Dart Impact
 Coefficient of Friction
 1% Secant Modulus (Stiffness)


4 mils
 0.050 gm/10 min
 0.923 gm/cc
 230 gms
 MD 24,000 psi
 MD 25,000 psi

ASTM D-1238
 ASTM D-1505
 ASTM D-1709
 ASTM D-1894 (unmodified film)
 ASTM D-882

RoHS Compliance Statement

None of the following materials are intentionally added in manufacturing this product: lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyls (PBB) or polybrominated diphenyl ethers (PBDE) as outlined in the Directive 2002/95/EC Article 4.1. See Protektive Pak Inc. letter on-line at ProtektivePak.com.

Item No.	Size (in.) W x L	Item No.	Size (in.) W x L
49100	2 x 3	49110	8 x 12
49101	3 x 4	49111	10 x 12
49102	3 x 5	49112	10 x 14
49103	4 x 6	49113	10 x 20
49104	5 x 7	49114	12 x 16
49105	5 x 8	49115	14 x 16
49106	6 x 8	49116	15 x 18
49107	6 x 9	49117	16 x 20
49108	6 x 10	49118	18 x 20
49109	8 x 10	49119	18 x 24
Packaged 100 per package			



Made in America

TRANSPARENT STATIC DISSIPATIVE (PINK POLY)

PROTEKTIVE PAK

PROTEKTIVE PAK
 13520 MONTE VISTA AVENUE, CHINO, CA 91710
 PHONE (909) 627-2578, FAX (909) 363-7331
ProtektivePak.com

DRAWING NUMBER
 49100

DATE:
 5/06