Rocker Switch Boots

E-SEEL[®] (Rock-R-Seel[™]) rocker switch boots are molded from RUBRGLAS[™] — APM's proprietary high tear-strength, transparent silicone rubber. These durable and flexible boots seal out dust, dirt, and moisture … without compromising switch operability, position status viewing or legend visibility. Each is designed to fully enclose the switch bezel, while our unique molded-in "panel sealing rib" forms a watertight and dust-tight seal against the front panel surface.

7

SPECIFICATIONS

Material: APM RUBRGLAS[™] (transparent silicone rubber), polymer type, ASTM D1418
Temperature Range: -80°F to +400°F
Operational Life: 50,000 actuations (minimum)
Resistant to: Salt spray, sunlight, ozone, weather, fungus, and most acids and lubricating oils
Agency Recognition: Rock-R-Seels[™] are UL-listed to UL Std. 50, types 1, 2, 4R, 5, 12, 12K, 13, and meet CSA standards
Shelf Life: Excess of 25 years

HOW TO ORDER


Specify APM boot part number.

| Photo # | E-SEEL Part # | Dimensions | | | | | | | | | | Compatible with |
|--------------|----------------------|--------------|----------------|---------------|----------------|----------------|----------------|----------------|----------------|--------------|----------------|--|
| | | А | | в | | с | | D | | Е | | These Rocker Switch Manufacturers |
| | | in. | mm | in. | mm | in. | mm | in. | mm | in. | mm | (Partial List) |
| 1 | C1111/7 | .359 | 9.13 | .609 | 15.48 | .937 | 23.81 | 1.703 | 43.26 | .900 | 22.87 | Consult Factory |
| 2 | C1113/62 | .297 | 7.54 | .797 | 20.24 | .687 | 17.46 | 1.093 | 27.78 | .968 | 24.61 | Arrow Hart – 2600 Series |
| 3 | C1113/63 | .297 | 7.54 | .406 | 10.32 | .687 | 17.46 | 1.093 | 27.78 | .515 | 13.10 | Arrow Hart – 2600 Series |
| 4 | C1113/66 | .228 | 5.79 | .348 | 8.84 | .531 | 13.46 | .750 | 19.05 | .531 | 13.49 | Carlingswitch #621 |
| 5 | C1113/70 | .297 | 7.54 | .437 | 11.11 | .875 | 22.23 | 1.218 | 30.96 | .640 | 16.27 | Carlingswitch RSC Series |
| 6 | C1113/71 C1113/80 | .413 .560 | 10.49 14.22 | .687 .750 | 17.46 19.05 | 1.046 1.375 | 26.59 34.92 | 1.327 1.750 | 36.51 44.45 | .703 .900 | 17.86 22.86 | Carlingswitch M Series Airpax R11 Eaton/Heinemann LC-1 Potter W-33 Carling LTI6 |
| 7 | C1113/75 | .413 | 10.49 | .687 | 17.46 | 1.046 | 26.59 | 1.437 | 36.51 | 1.390 | 35.32 | Carlingswitch M Series Airpax R21 Eaton/Heinemann LC-2 |
| Not Shown | C1213/53 C1213/60 | .312 .350 | 9.14 10.16 | .700 1.000 | 19.81 21.08 | .700 .820 | 19.81 21.08 | 1.120 1.120 | 29.21 29.21 | .800 .800 | 23.11 23.11 | Oslo S Series Oslo S Series |



5

6



DIMENSIONS FOR REFERENCE ONLY.



Carlingswitch M Series Rocker Actuator Switch with C1113/71 E-SEEL