


- NOTES:
1. ALL DIMENSIONS IN MM [INCH]
  2. GENERAL TOLERANCE: X.X=±0.4  
X.XX=±0.25
  3. TERM. NOS. FOR REFERENCE ONLY.
  4. RATING: 1A @125VAC, 0.5A @250VAC
  5. CONTACT RESISTANCE: 20mILLI-OHMS
  6. DIELECTRIC STRENGTH: 1500 VAC-1Minute
  7. INSULATION RESISTANCE: 200 Mega-OHMS min.
  8. MATERIALS:

HOUSING: ZINC ALLOY DIE CAST  
 CYLINDER: ZINC ALLOY W/CHROME PLATING  
 TERMINAL AND CONTACTS: SILVER PLATED  
 KEYS (2) KEY CODE 102: TUBULAR  
 ZINC ALLOY, CHROME PLATING

**LEGEND**

⊙ = INDICATES KEY PULL POSSIBLE



SWITCH FUNCTION	POS 1	POS 2
↕	↕	↕
↔	↔	↔

**E-SWITCH®**

RECOMMENDED PANEL CUTOUT

B	12174	REVISED SCHEMATIC	5/22/02	CJB
A	11746	RELEASED FOR PRODUCTION	10/16/01	CJB
REV.	ECN No.	DESCRIPTION	DATE	CHKD

TITLE		SCALE	DATE	DR	DWG	REV
K01064-102		1.5:1	10/16/01	CJB	K100302	B

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED