


RECOMMENDED PANEL LAYOUT



CIRCUIT: DP (45° INDEXING)
CONTACT CONFIGURATION

SWITCH FUNCTION		
CONNECTED TERMINAL #	POS. 1	POS. 2
8-1	1-2	7-8

LEGEND
 ● =Detent Positions (45° or 90°)
 ⊙ =Key pull possible in these positions

- NOTES:
1. ALL DIMENSIONS IN MM [INCH]
 2. GENERAL TOLERANCE: X.XX=±0.4
X.XX=±0.25
 3. TERM. NOS. FOR REF. ONLY
 4. CONTACT RATING: 4A @125VAC/28VDC, 2A @250VAC
 5. CONTACT RESISTANCE: Below 10 milliohms
 6. DIELECTRIC STRENGTH: 1kV RMS min. at sea level
 7. ELECTRICAL LIFE: 10,000 make-and-break cycles at full load.
 8. DESIGNATE MAJOR FEATURES
 9. MATERIALS:

CONTACTS: Silver Plated CU (Q Contact material)
 TERMINALS: GOLD FLASH Over Silver (Q Contact material)
 MOUNTING NUT: Nickel Plated zinc alloy
 CONTACT SPRING: Piano Wire
 KEYS: (2 Keys) Brass with code no. A126



REV.	ECN NO.	DESCRIPTION	DATE	CHKD
A	11211	RELEASED FOR PRODUCTION	2/01/01	CJB

TITLE		SCALE	DATE	DR	DWG	REV
K01301 (Key Code No. A126)		1:1	2/01/01	CJB	K200218	A

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED