


CONTACT CONFIGURATION



NOTES:

1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: X.X=±0.4
X.XX=±0.25
3. TERM. NOS. FOR REFERENCE ONLY.
4. CONTACT MATERIAL: COPPER ALLOY W/ SILVER PLATE
5. RATING: 7A@125V, 4A@250
6. CONTACT RESISTANCE: 20MΩ MAX @ 5V DC 1A
7. DIELECTRIC STRENGTH: AC 1500V RMS
8. OPERATING FORCE: 550±150gf TYP.
9. TRAVEL: FULL:5.5, LOCK:4.0

D	15234	UPDATED DESCRIPTION	9/2/05	PH
C	11768	REVISED DIMENSION	5/29/02	CB
B	11768	REVISED, AND REDRAWN	10/23/01	CJC
REV.	ECN NO.	DESCRIPTION	DATE	CHKD

E-SWITCH®

TITLE: P227 EE 1CX

SCALE: 1.5:1 DATE: 10/23/01 DR: CJC DWG: P030113 REV: D

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSMITTED