



ISOMETRIC

| Parts List | | | |
|------------|-----|-------------|-----------------------------------------|
| ITEM | QTY | PART NUMBER | DESCRIPTION |
| 1 | 1 | F060602 | LASEEV11 |
| 2 | 1 | F051702 | 25MM RING FOR LA SERIES |
| 3 | 1 | F060202 | 25MM GREEN LENS |
| 4 | 1 | F050404 | 50-004-04 14VAC OR DC INCANDESCENT BULB |

- NOTE:
- ALL DIMENSIONS IN MM [INCH]
 - GENERAL TOLERANCE: X.X=±0.4
X.XX=±0.25
 - TERMINAL NUMBERS FOR REF ONLY
 - RATING: 5 AMPS @ 250VAC UL, VDE APPROVED
6 AMPS @ 24VDC UL, VDE APPROVED
 - ELECTRIC LIFE: 50,000 MAKE-AND-BREAK CYCLES AT FULL LOAD.
 - INSULATION RESISTANCE: 1,000 MEGA-OHM MIN.
 - OPERATING TEMP.: -25°C to 55°C
 - LAMP VOLTAGE: 14VAC OR DC INCANDESCENT
 - ▲DENOTES CRITICAL PARAMETER.

E-SWITCH®

| | | | | |
|-----|--------|-------------------------|--------|----|
| A | 15744 | RELEASED FOR PRODUCTION | 2/9/06 | PH |
| REV | PCR NO | DESCRIPTION | DATE | BY |

| | | | | |
|--------------------|----------|----|---------|-----|
| TITLE LASEEV11BGRN | | | | |
| SCALE | DATE | DR | DWG | REV |
| 1.5:1 | 2/9/2005 | PH | XF0670P | A |

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED