



- NOTE:
1. ALL DIMENSIONS IN MM [INCH]
 2. GENERAL TOLERANCE: X.X=±0.4
X.XX=±0.25
 3. TERM. NOS. FOR REFERENCE ONLY.
 4. RATING: 7A@125VAC, 4A@250VAC UL, CUL, & VDE APPROVED
 - ▲ 5. CONTACT MATERIAL:
TERMINALS, COPPER ALLOY SILVER PLATE.
CONTACTS, COPPER ALLOY W/TIN OXIDE
 6. CONTACT RESISTANCE: 100MILLI-OHMS MAX.
 7. DIELECTRIC STRENGTH: 1000VAC for 1min
 8. ELECTRICAL LIFE: 6,000 CYCLES
 9. OPERATING FORCE: 550±150gf TYP.
 10. TRAVEL: FULL: 5.5±0.2mm, LOCK: 4.0±0.2mm
 11. ▲DENOTES CRITICAL PARAMETER
 12. 2002/95/EC (ROHS) COMPLIANT

E-SWITCH®

A	16044	RELEASED FOR PRODUCTION	5/23/06	CT
REV	PCR NO	DESCRIPTION	DATE	BY

TITLE P227EE2A18ATAGBLK				
SCALE	DATE	DR	DWG	REV
1.5	5/23/2006	CT	XP0287A	A

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED