



- NOTES:
1. ALL DIMENSIONS IN MM [INCH]
 2. GENERAL TOLERANCE: X.X=±0.4
X.XX=±0.25
 3. TERM. NOS. FOR REFERENCE ONLY.
 4. RATING: 7A@125V, 4A@250 VUL,CUL, & VDE APPROVED
 5. CONTACT MATERIAL:
Terminals, Copper Alloy W/Silver plate.
Contacts, Copper Alloy W/Tin Oxide
 6. CONTACT RESISTANCE: 100milli-ohms TYP. MAX Initial
 7. DIELECTRIC STRENGTH: 1500V for 1min
3000V between poles
 8. ELECTRICAL LIFE: 6,000 Cycles
 9. OPERATING FORCE: 550±150gf TYP.
 10. TRAVEL: FULL:5.5, LOCK:4.0
 11. 2002/95/EC (ROHS) COMPLIANT
 12. ▲ DENOTES MAJOR DIMENSION

| | | | | |
|------|---------|-------------------------|---------|------|
| B | 16913 | FIXED DESCRIPTION | 1/24/07 | TN |
| A | 13192 | RELEASED FOR PRODUCTION | 6/6/03 | AR |
| REV. | ECN No. | DESCRIPTION | DATE | CHKD |

| | | | | | | |
|-------------|--|-------|---------|----|---------|-----|
| TITLE | | SCALE | DATE | DR | DWG | REV |
| P227EE2A20B | | 1.5:1 | 1/24/07 | TN | P030110 | B |



THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED