


RECOMMENDED PANEL MOUNT  
7MM MAX THICKNESS  
SCALE 1:1



NOTES:

1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: X.X=±0.4  
X.XX=±0.25
3. TERM. NOS. FOR REF. ONLY
4. RATING: 3A 125V, 1.5A 250V AC, UL & CUL APPROVED
5. CONTACT RESISTANCE: 50m ohm max.
6. INSULATION RESISTANCE: DC 500V 100Mega Ohm min.
7. DIELECTRIC STRENGTHS: AC 1500V 1 minute
8. GREEN LED 3VDC
9. ▲ DENOTES CRITICAL PARAMETER.

REV.	ECN No.	DESCRIPTION	DATE	CHKD
D	14419	ADD LED VOLTAGE	10/21/04	AR
C	14212	ADD LED TO CIRCUIT DIAGRAM	8/3/04	AR
B	14157	UPDATE DIMS, TITLE, ADD LOGO	7/9/04	AR
A	14138	RELEASED FOR PRODUCTION	7/2/04	AR

**E-SWITCH®**

TITLE  
**RP3508ABLKGRNGRNNNS**

SCALE	DATE	DR	DWG	REV
1.5:1	7/2/04	AR	F130422	D

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED