


RECOMMENDED PANEL MOUNT
7MM MAX THICKNESS
SCALE 1:1



CIRCUIT: SPST

NOTES:

1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: X.X=±0.4
X.XX=±0.25
3. TERM. NOS. FOR REF. ONLY
4. RATING: 3A 125V, 1.5A 250V AC, UL & CUL APPROVED
5. CONTACT RESISTANCE: 50m ohm max.
6. INSULATION RESISTANCE: DC 500V 100Mega Ohm min.
7. DIELECTRIC STRENGTHS: AC 1500V 1 minute
- ▲ 8. NO LED
9. ▲ DENOTES CRITICAL PARAMETER.

C	14157	UPDATE DIMS, TITLE, ADD LOGO	7/9/04	AR
B	13857	ADD LOGO AND INFO	3/22/04	AR
A	13855	RELEASED FOR PRODUCTION	3/19/04	AR
REV.	ECN No.	DESCRIPTION	DATE	CHKD

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED

E-SWITCH®				
TITLE RP3508BBLKREDNNS				
SCALE	DATE	DR	DWG	REV
1.5:1	3/19/04	AR	F130417	C